FORM 9-331A (FEB. 1951)

DISTR

(SUBMIT IN TRIPLICATEPPY to: Roswell

LAND OFFICE IC 066097 NMOCCIZ) LEASE NO. Humble 205649

EPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

UNITED STATES

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS  NOTICE OF INTENTION TO TEST WATER SHUT-OFF  NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL  NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Huapache Oil Unit	2	Hobbs,	New Mexico	February 7	. 19_63
WELL NO. 10 IS LOCATED	1980_FT. FRO	om $\binom{N}{x}$ line	AND 1980 FT. FR	$\cos\left\{rac{\mathbf{x}}{\mathbf{w}}\right\}$ line of se	c. 10
SE/4 of NW/4	23 <b>-</b> S	22 <b>-</b> E		R E	DEIVED
(14 SEC. AND SEC. NO.)	(TWP.)	(RANGE)	(MERIDIAN)		•
Huapache Area W/C	Edc (count	Y OR SUBDIVISION)	Ne	STATE OR TERRITORY)	EB 4 1963

THE ELEVATION OF THE DERRICK FLOOR ABOVE SEA LEVEL IS Later FT.

C.C.C.

## DETAILS OF WORK

(STATE NAMES OF AND EXPECTED DEPTHS TO OBJECTIVE SANDS; SHOW SIZES, WEIGHTS, AND LENGTHS OF PROPOSED CASINGS; INDICATE MUDDING JOBS,

Spudded 13-3/4" hole 12:00 noon 1-27-63. Ran 933' (29 jts) 10-3/4" 40.5# J-55 csg, set at 954. Cemented with 500 sacks Incor 12% gel cement, w/12-1/2# Gelsonite, 1/4# flocele per sack and 200 sacks Incor neat w/12.5# Gilsonite, 1/4# Flocele per sack. POB 1:15 PM, 1-31-63. Cement circulated, tested casing a/800# for 30 minutes, no drop in pressure. Drilled plug 1:00 PM, 2-1-63.

I UNDERSTAND THAT THIS PLAN OF WORK MUST RECEIVE APPROVAL IN WRITING BY THE GEOLOGICAL SURVEY BEFORE OPERATIONS Humble Oil & Refining Company ADDRESS P. O. Box 2347 Hobbs. New Mexico