

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Form Approved.	
Land Office	10 066097
Lease No	Humble 205649
Unit	7
•	ESEIVER

	AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	. [
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUFFLERICAL WELL HISTORY
(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	•
Huapache Oil Unit	Hobbs, New Mexico April 26, 1963
	om N line and 1980 ft. from W line of sec. 10
SE/4 of NI/4	(Range) (Meridian)
Huanache Area W/C	New Mexico
(Field) (Count	ty or Subdivision) (State or Territory) O)
he elevation of the derrick floor above sea	O ≥ 3 ≥
	AILS OF WORK sizes, weights, and lengths of proposed casings; indexe mudding jobs coment- ill other important proposed work)
tate names of and expected depths to objective sands; show ing points, and a Drilled to total depth of 10150.	Sizes, weights, and lengths of proposed casings; indexe mudding jobs coment- ill other important proposed work) Ran 10132' (318 Jts) 4-1/2" casing set at
Drilled to total depth of 10150. Cement with 500 sxs reg	Man 10130' (318 Jts) 4-1/2" casing set at 12% gel plus 1/4# HR-7 per sack plus 5# Gil-
Drilled to total depth of 10150. Cement with 500 sxs reg	Sizes, weights, and lengths of proposed casings; indexe mudding jobs coment- ill other important proposed work) Ran 10132' (318 Jts) 4-1/2" casing set at
Drilled to total depth of 10150. 10,150. Cement with 500 sxs reg	Man 10130' (318 Jts) 4-1/2" casing set at 12% gel plus 1/4# HR-7 per sack plus 5# Gil-
Drilled to total depth of 10150. 10,150. Cement with 500 sxs regionite per sack followed with 200 cement did not circulate.	Man 10130' (318 Jts) 4-1/2" casing set at 12% gel plus 1/4% MR-7 per sack plus 5% Gil- examinat 5000' - temp survey. WOC. Tested case
Drilled to total depth of 10150. 10,150. Cement with 500 sxs reg sonite per sack followed with 200 cement did not circulate. Top of	Man 10130' (318 Jts) 4-1/2" casing set at 12% gel plus 1/4% MR-7 per sack plus 5% Gil- examinat 5000' - temp survey. WOC. Tested case
Drilled to total depth of 10150:. 10,150: Cement with 500 sxs regionite per sack followed with 200 Cement did not circulate. Top of with 1500% pressure for 30 minutes.	sizes, weights, and lengths of proposed casings; ind community community of the community o
Drilled to total depth of 10150:. 10,150: Cement with 500 sxs reg sonite per sack followed with 200 Cement did not circulate. Top of with 1500# pressure for 30 minutes	sizes, weights, and lengths of proposed casings; ind community commentation in proposed work) Ram 10130' (318 Jts) 4-1/2" casing set at 12% get plus 1/4% HR-7 per sack plus 5% Gil- 2xs slc set neat cement. POB 6:00 P.M. 4-25-6 memont 6000' - temp survey. WOC. Tested casing set at 1 in writing by the Geological Survey before operations may be commenced.
Drilled to total depth of 10150. 10,150. Cement with 500 sxs reg sonite per sack followed with 200 cement did not circulate. Top of with 1500% pressure for 30 minutes. I understand that this plan of work must receive approva	sizes, weights, and lengths of proposed casings; ind community commentation in proposed work) Ram 10130' (318 Jts) 4-1/2" casing set at 12% get plus 1/4% HR-7 per sack plus 5% Gil- 2xs slc set neat cement. POB 6:00 P.M. 4-25-6 memont 6000' - temp survey. WOC. Tested casing set at 1 in writing by the Geological Survey before operations may be commenced.
Drilled to total depth of 10150:. 10,150: Cement with 500 sxs reg sonite per sack followed with 200 Cement did not circulate. Top of with 1500% pressure for 30 minutes	sizes, weights, and lengths of proposed casings; ind community commentation in proposed work) Ram 10130' (318 Jts) 4-1/2" casing set at 12% get plus 1/4% HR-7 per sack plus 5% Gil- 2xs slc set neat cement. POB 6:00 P.M. 4-25-6 memont 6000' - temp survey. WOC. Tested casing set at 1 in writing by the Geological Survey before operations may be commenced.