

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER INDICATED*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

HM-003730

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Copy to 7

7. UNIT AGREEMENT NAME

Wagonfire Unit

8. FARM OR LEASE NAME

Wagonfire Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Chaparral Area Wilcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-23-23, HM

12. COUNTY OR PARISH

Edley

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Shell Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 1050, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface1000' FSL & 1000' FSL, Sec. 17, T-23-S, R-23-E, Edley
County, New Mexico.

14. PERMIT NO.

Blanket

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4210 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other)

☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.)*

Run 2 1/2" of 5/8" (30, J-99) casing and mud at 2000' with 300 sacks neat
plus 0% gel and 200 sacks neat + 2% CaCl₂. Cement did not circulate. Plug
down at 7:30 P.M. (MST), April 13, 1964. Run temperature survey and found
cement top at 300'. Run 1" casing in annulus to 275' and cemented with 100
sacks regular neat + 2% CaCl₂. After WOC 48 hours, tested casing with 3000 psi
for 30 minutes - no pressure drop.

RECEIVED
APR 29 1964
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICORECEIVED
MAY 1 1964
D. C. E.
ALBUQUERQUE FIELD

18. I hereby certify that the foregoing is true and correct

Original Signed By
SIGNED R. J. DOWDTITLE Division Mechanical Engineer DATE 4-27-64

(This space for Federal or State office use)

APPROVED BY
APR 29 1964
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

R. L. BEENWALD
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.