

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

SEP - 8 '94

2. Name of Operator

Barbara Fasken

O. C. D.

3. Address and Telephone No.

303 W. Wall, Suite 1900, Midland, TX 79701

ARTESIA, OFFICE

(915) 687-1777

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 1980' FSL & 1980' FWL, Sec. 17, T-23-S, R-23-E

5. Lease Designation and Serial No.

NM-3597

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Mershon "17" Federal #1

9. API Well No.

30-015-10368

10. Field and Pool, or Exploratory Area

Chaves Undes. Penn

11. County or Parish, State

Eddy

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other _____
-
- ☒
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to plug and abandon well as follows:

1. POW w/4½" pkr. and 2-3/8" tbg.
2. Set 4½" CIBP on wireline @ 9615'.
3. RIW w/tbg. and displace well w/mud laden brine water. Spot 10 sx Class "H" @ 9615'. POW w/tubing.
4. Freepoint 4½" csg., cut off and recover estimated 7000' of casing.
5. Spot Class "H" plugs as follows: (s.w. 16.4 ppg, yield 1.06 cuft/sk)
 - a. 25 sx @ 7050' (50' inside 4½" stub). TAG THIS PLUG
6. Spot Class "C" plugs as follows: (s.w. 14.8 ppg, yield 1.32 cuft/sk)
 - a. 30 sx @ 6450'
 - b. 40 sx @ 2050' (9-5/8" shoe plug). TAG THIS PLUG.
 - c. 30 sx @ 327' (13-3/8" shoe plug).
 - d. 20 sx @ 50' surface plug
7. Cut off casing 3' below ground level and erect marker.
8. Remove all equipment, rip and reseed location with BLM approved seed.

14. I hereby certify that the foregoing is true and correct

Signed Jimmy LARATitle Operations Supt.Date 8-12-94

(This space for Federal or State office use)

(ORIG. SGO.) JOE G. LARA

Title PETROLEUM ENGINEERDate 9/6/94

Approved by

Conditions of approval, if any: See attached

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side