

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT 1. RIPLICATE*
(Other instructions on
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

WM 0471398-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME Hess Hills Unit
2. NAME OF OPERATOR Tenneco Oil Company	8. FARM OR LEASE NAME Hess Hills Unit
3. ADDRESS OF OPERATOR P. O. Box 1031 Midland, Texas	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2128.5 FSL & 1930 FSL, Sec. 34, T-23-S, R-23-E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T-23-S, R-23-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4375.7 GR	12. COUNTY OR PARISH Deaf
	13. STATE N. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to TD of 11,500'

Persuant to verbal approval to Frank Poole from Jim Kraut, propose to plug well as follows:

Set cement plugs as follows: 11,050-10,900, 10,200-10,050, 8950-8800, 7900-7750, 6900-6750, 4925-4775, 2580-2430, & 30-surface.

Mud with the following properties will be left between the plugs:

Weight - 9.7 lb/gal.

Viscosity - 35 sec./1000 cc.

Water Loss - 7.0 cc/30 min.

The 3 3/4" casing @ 2504 will be left in the hole.

A marker will be erected at the surface.

RECEIVED

RECEIVED

RECEIVED

NOV 3 1966

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

NOV 2 1966

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED *J. P. Carnes*

J. P. Carnes

TITLE Dist. Prod. Eng.

DATE 10-26-65

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

APPROVED
3 1966
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED 1964

APR 10 1964

U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT