

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/-
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 1 1967

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Morris R. Antweil		8. Farm or Lease Name Missouri-N.M. LandCo.	
3. Address of Operator P. O. Box 2010 Hobbs, New Mexico		9. Well No. 1	
4. Location of Well UNIT LETTER O 990 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 6 TOWNSHIP 23S RANGE 27E NMPM.		10. Field and Pool, or Wildcat Wildcat	
15. Elevation (Show whether DF, RT, GR, etc.) 3217 KB		12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran and cemented 8-5/8", 24 & 32#/ft, new intermediate casing at 2592' with 750 sxs. Cement circulated, plug down 6:45 AM 9/7/67. Tested casing with 1000 psig for 30 mins. No pressure decline. Cemented with 500 sxs regular / 4% gel and 250 sxs regular cement with 2% Calcium Chloride. WOC 30 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>Burton Veto</i>	TITLE Agent	DATE 9-8-67
APPROVED BY <i>R. F. Ham</i>	TITLE INSPECTOR	DATE SEP 18 1967
CONDITIONS OF APPROVAL, IF ANY:		