

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Caroline Hunt Lands</u>		Lease <u>J.B. Joyce</u>		Well # <u>1</u>	
Location of Well	Unit <u>D</u>	Section <u>28</u>	Township <u>23</u>	Range <u>23</u>	County <u>Eddy</u>
Drilling Contractor	<u>Winton Drilling Co</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15</u>	<u>11 3/4</u>	<u>47</u>		<u>375</u>	<u>115</u>
<u>10</u>	<u>8 7/8</u>	<u>44</u>		<u>240</u>	<u>145</u>
<u>1 1/2</u>	<u>5</u>	<u>40</u>		<u>10</u>	<u>25</u>

Casing Data:

Surface 79 joints of 8 7/8 inch 24 # Grade J5
(Approved) ~~XXXXXXXX~~

Inspected by L. Hunt date 10-30-67

Cementing Program

Size of hole 11 3/4 Size of Casing 8 7/8 Sacks cement required

Type of Shoe used Guide Float collar used - Btm 3 jts welded Thread Lok

TD of hole 2475 Set - Feet of 8 7/8 Inch 24 # Grade J

New-used csg. @ TD with 200 sacks neat cement around shoe
+ 900 sax 50-50 Pz additives Class C

Plug down @ 2130 (AM) (PM) Date 11-1-67

Cement circulated No No. of Sacks

Cemented by Hall, Burton (Operator) Witnessed by L. Hunt

Temp. Survey ran @ 10:30 (AM) (PM) Date 11-1-67 top cement @ 650

Casing test @ - (AM) (PM) Date

Method Used - Witnessed by -

Checked for shut off @ - (AM) (PM) Date

Method used - Witnessed by -

Remarks: Ran 1st to 614' 1:25 PM 50SX C 4% CaCl + 1 bag Fluoride
w. 228 feet of L.H. 4:15 PM 50SX as above filled to 240
feet. 8:55 PM circ hole with 50SX C 2% CaCl

Water. Picked up strikers from 375 to 700'. Filled 2.4