

DELCO PETR CORP.
 LAMES RANCH UNIT No. 3
 WELL DIAGRAM

RECEIVED

MAY 23 1973

O. C. C.
 ARTESIA, OFFICE

2 7/8" EUE N-80
 TGA

16" @ 475' K.B.
 CEMENTED w/ 650 SX.
 DOWELL LITE WATE.
 CNT CIRC.

10 3/4" @ 3890' w/
 w/ 2400 SX HONCO LITE

TOP OF CEMENT 3660'

DV TOOL @ 6586'

7 5/8" - 29.70" S-95 @ 12,037'
 1ST STAGE - 2050 SX.
 2ND STAGE - DV TOOL @ 6586'
 & CEMENTED w/ 1000 SX

BAKER Model "L"
 SLEEVE

STRAWN PERFORATIONS 12,731-7325

2 7/8" EUE N-80 TGA

BAKER HYDROSTATIC PKR @

@ 12,847'
 BAKER Model "B" PLUG

ATOKA PERFORATIONS - 12,998'-13,005'

BAKER 1.07" FSP "P" BLANKING PLUG

BAKER Model "L"
 SLEEVE

BAKER Model "D" PKR @ 13,750'

BAKER "ER"
 REOPTICAL

MCCON PERFORATIONS - 13,862-72, 13,835-842

MCCON PERFORATIONS 14,062-68, 14,261-66,
 & 14,204-56

P.B.T.D. - 15,100'

5 1/2" 23# Q-75 SFJP LINER.
 TOP OF LINER @ 11,712' - BOTTOM @ 15,450'
 CEMENTED w/ 650 SX. CLASS "H" CNT.

TOP OF DEVONIAN 15,453'

T.D. 15,595'

RECEIVED
 MAY 23 1973
 U. S. GEOLOGICAL SURVEY
 ARTESIA, NEW MEXICO