

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-3852

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

RECEIVED

OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

MAR 04 1981

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

O. C. D.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2310' FSL & 2310' FWL

Unit-K

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Boothe "B0" Federal Corn

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Rock Tank Morrow Lower

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 12-T23S-R24E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4008'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) Amended P&A

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

As approved by Peter Chester of USGS-Roswell, will cut and pull 5½" casing at 7350'. Circulate hole with abandonment mud. Spot 200' from 7450' (from 100' inside of 5½" casing) up to 7250'. Spot 150' cement plug 6100'-5950'. Spot 150' cement plug 4250'-4100'. Spot 150' cement plug 2575'-2425'. Spot 100' surface plug. Install dry hole marker; clear and clean location as required by USGS.

RECEIVED
MAR 07 1981
USGS

18. I hereby certify that the foregoing is true and correct

SIGNED

P. W. CHESTER

TITLE

Area Engineer

DATE

3-3-81

(This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER

APPROVED BY

MAR 9 1981

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side