

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	2
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

SEP 10 1970

STATE ☒ FEDERAL ☒

SEE 10-15-68

APPLICATION FOR PERMIT TO DRILL, DEEPEN OR PLUG BACK

1a. Type of Work DRILL ☒ DEEPEN ☐ PLUG BACK ☐		2. Date of Approval
b. Type of Well OIL WELL ☒ GAS WELL ☐ OTHER ☐		3. Name of Operator
Union Oil Company of California		Tracy
4. Address of Operator P. O. Box 671 Midland, Texas 79701		3
5. Location of Well UNIT LETTER M LOCATED 550 FEET FROM THE South		Undesignated
AND 610 FEET FROM THE West LINE OF SEC. 3 T4S. 22-S 27-E		Eddy
6. Proposed Depth		7. Formation
3550		Delaware
8. Method of Drilling		9. Rotary
Contract not let		On approval
10. Type of Plug (Blanket, etc.)		11. Status of Plug
Unknown		Blanket

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11"	8-5/8"	24#	550'	200	Circ. to surface
7-7/8"	4-1/2"	9.5#	3550'	300	2650'

3000 psi double manual preventers

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,
EXPIRES 12-10-70

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed J. R. Gray Title District Drilling Supt. Date September 8, 1970

(This space for State Use)

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE SEP 10 1970

CONDITIONS OF APPROVAL, IF ANY:

1. The operator shall maintain contact with the surface while running the 4 1/2" casing

Cement must be circulated to surface behind the casing