Yates Petroleum Corporation Medano "VA" State #1 K 16-23S-31E

Attachment A Page 1

- III. Well Data
 - A. 1. Lease Name/Location: Medano "VA" State #1 K 16-23S-31E 1947' FSL & 1986' FWL
 - 2. Casing Strings:
 - a. Present Well Condition 20" 94# H40 @ 624' w/1060 sx (circ) 13-3/8" 61# S80 @ 4139' w/3400 sx (circ) 9-5/8" 43.5#, 53.5# N80, P110 @ 12444' w/4150 sx (circ) 7-5/8" 39# P110 liner @ 12257-14153' w/250 sx 2-7/8" 6.5# N80 tubing @ 4300'

Present TD: 9715', PBTD: 5900'

- 3. Proposed well condition: Casing same as above 2-7/8" 6.5# N80 production tubing at 4300' 2-7/8" 6.5 N80 plastic-coated injection tubing @ 5950'
- 4. Propose to use Guiberson or Baker plasticcoated or nickel-plated packer set at 5950'.
- B. 1. Injection Formation: Cherry Canyon Brushy Canyon Bone Spring
 - 2. Injection Interval will be through perforations from approximately 6019-8639'.
 - 3. Well was originally drilled as an exploratory Morrow gas well. Well will be dual Delaware producer (4218-4237') and Cherry Canyon (6019-6680'), Brushy Canyon (6996-7860'), and Bone Spring (8065-8639') water disposal well when work is completed.
 - 4. Perforations: a. 14117-14126' Morrow, CIBP 14100' + 10 sx cmt