

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

O. O. O.
APTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator CITIES SERVICE OIL COMPANY		8. Farm or Lease Name Merland B Com.
3. Address of Operator P.O. Box 69, Hobbs, New Mexico 88240		9. Well No. 1
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM East 30 THE LINE, SECTION 22S RANGE 27E NMPM.		10. Field and Pool, or Wildcat S. Carlsbad Morrow Undes.
15. Elevation (Show whether DF, RT, GR, etc.) 3200 GR (EST.)		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD336 Anhydrite. Prep. to drill. Spud @ 7:30 a.m. on 5-15-71. Ran 10 jts. (317') 13 3/8" OD 48# H-40 casing. Set and cemented @ 335 w/300 sacks Class "C" w/2% CaCl₂ cement. Plug down @ 12:40 a.m. on 5-16-71. Circulated 50 sacks cement. WOC 24 hrs. Tested 13 3/8" casing and rams to 1000 psi for 30 min. with no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED ORIGINAL SIGNER C. D. ROBERTSON TITLE Dist. Admin. Supervisor DATE May 20, 1971

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE MAY 21 1971

CONDITIONS OF APPROVAL, IF ANY: