

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO **RECEIVED** OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE <input type="checkbox"/>	FEE <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		8. Farm or Lease Name Randall	
2. Name of Operator Morris R. Antweil		9. Well No. 1	
3. Address of Operator Box 2010 Hobbs, New Mexico		10. Field and Pool or Wildcat S. Carlsbad (Morrow)	
4. Location of Well UNIT LETTER K LOCATED 1864 FEET FROM THE South LINE AND 2005 FEET FROM THE West LINE OF SEC. 21 TWP. 22-S RGE. 27-E NMPM		12. County Eddy	
19. Proposed Depth 11,800'		19A. Formation Morrow	
20. Rotary or C.T. Rotary		21. Elevations (Show whether DF, RT, etc.) 3120' GL	
21A. Kind & Status Plug. Bond Blanket		21B. Drilling Contractor Delta Drilling	
22. Approx. Date Work will start 30 November, 1971			

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2"	13 3/8"	48#	350'	375 sx	Circ.
12 1/4"	9 5/8"	36 & 40#	5300'	850 sx.	1900'
8 3/4"	7"	23, 26 & 29#	11,800'	575 sx.	9000'

BOP Program:

- 1 - 10" Series 1500 Cameron, QRC
- 1 - 10" Series 1500 Cameron, SS

Mud program as required - estimated maximum mud wt. 10.7#/gal.

NOT VALID UNLESS
ENTERED COMMENCED,
EXPIRES

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed R M Williams Title Agent Date 26 November, 1971

(This space for State Use)

APPROVED BY W. A. Sweeney TITLE _____ DATE 1971

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface before casing