

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JUL 1 1972

BUREAU
ARTERIAL

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> WELL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -----
2. Name of Operator Morris R. Antweil	8. Farm or Lease Name Randall
3. Address of Operator Box 2010, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER K 1864 FEET FROM THE South LINE AND 2005 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 22-S RANGE 27-E NMPM.	11. Field and Pool, or Unit Name Morrow-Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3120' GL	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Completion Attempt

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11,895' PBTD 11,770'
Perforated 4-1/2" liner 11,496' - 11,647' (12 holes). Set Baker Model "F" packer @ 11,430'. Swabbed down. Show of gas. Treated w/500 gals. mud acid containing 15% alcohol. 2-1/2 b/m. @ 3600 psi. Swabbed and flowed gas TSTM. Treated w/4250 gals. acid containing 15% alcohol, 3 b/m @ 5100 psi. ISIP 3000 psi. 15-min SIP 1800 psi. Flowed gas TSTM. Flow tested on intermitter at limited rates and low FTP. Pulled tubing. Set Baker Model "N" Bridge Plug @ 10,100' in 7" casing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *R. M. Williams* TITLE Agent DATE 30 June 1972

APPROVED BY *W. A. Gussitt* TITLE 8 11 1972 DATE 30 June 1972
CONDITIONS OF APPROVAL, IF ANY: