

OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUN 24 1976

O. C. C.

ARTESIA, OFFICE

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. -----
7. Unit Agreement Name -----
8. Farm or Lease Name Randall
9. Well No. 1
10. Field and Pool, or Wildcat San Juan Carlsbad Canyon
12. County Eddy

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Morris R. Antweil 3. Address of Operator P. O. Box 2010 Hobbs, New Mexico 88240 4. Location of Well UNIT LETTER K 1864 FEET FROM THE South LINE AND 2005 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 22-S RANGE 27-E N.M.P.M. 15. Elevation (Show whether DF, RT, GR, etc.) 3120' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged and abandoned as follows:

1. Spotted 15 sx cement plug on bridge plug at 10,100'.
2. Spotted 25 sx cement plug across purfs at 9930'.
3. Shot and pulled 5150' of 7" casing.
4. Spotted 45 sx cement plug at 5150' in 9-5/8" csg.
5. Shot and pulled 800' 9-5/8" casing.
6. Spotted 80 sx cement plug across 9-5/8" stub.
7. Spotted 85 sx cement plug across 13-3/8" shoe at 375'.
8. Spotted 10 sx surface plug with marker.

P & A June 4, 1976

Produced for H
ID
6-30-76

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. M. Williams TITLE Agent DATE June 22, 1976

APPROVED BY _____ TITLE OIL AND GAS INSPECTOR DATE AUG 24 1976

CONDITIONS OF APPROVAL, IF ANY: