

N. M. O. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR
(Other instruct
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0540701-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Drag-A

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Carlsbad, South (Morrow) Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18, 23-S, 27-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Phillips Petroleum Company ✓

3. ADDRESS OF OPERATOR
Room 711, Phillips Building, Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
660' FN and 1980' FW Lines

14. PERMIT NO. --

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
later

RECEIVED

MAR 5 1972

OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT.

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud well

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MI & RU Warton Drilling Company rotary. Spudded 17-1/2" hole at 5 PM, 3-22-72. Drilled to 370', conditioned hole. Set 10 joints (370 feet) 13-3/8" O.D., 48#, H-40, ST&C, A-condition casing at 370', Howco cemented w/450 sx Class H cement w/2% CaCl₂ and 1/4# Flocele/sx. Plug to 335' w/53 BW at 300#. Circulated 30 sx cement. Job complete 2:30 AM 3-23-72. WOC 18 hrs, tested casing w/800# for 30 minutes, OK. Drilled cement from 310' to 370', started drilling ahead at 370' with 11" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Senior Reservoir Engineer DATE 3-28-72

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAR 29 1972
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side