

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved
Budget Bureau No. 42-R1424
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|---|--|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME --- |
| 2. NAME OF OPERATOR Phillips Petroleum Company | 7. UNIT AGREEMENT NAME --- |
| 3. ADDRESS OF OPERATOR Room 711, Phillips Building, Odessa, Texas, 79761 | 8. FARM OR LEASE NAME Drag-A |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FN and 1920' FW lines | 9. WELL NO. 1 |
| 14. PERMIT NO. --- | 10. FIELD AND POOL, OR WILDCAT Carlsbad, South (Morrow) Gas |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3217' Gr., 3237' DF | 11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA 18, 23-S, 27-E |
| | 12. COUNTY OR PARISH Eddy |
| | 13. STATE N. Mexico |

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Packer Setting Affidavit

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

On May 15, 1972, Set Baker Model F-1 production separator packer at 11,470', separating Morrow and Atoka reservoirs for conventional dual completion with Morrow zone-Carlsbad, South (Morrow)-produced through 2-7/8" tubing latched into packer, and with Atoka zone-Carlsbad, South (Atoka)-produced through the tubing - casing annulus.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE Senior Reservoir Engineer

DATE 6-5-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE