		T OF THE INTER	IOD (Other inst	T JCATE*		red. au No. 42-R1
		T OF THE INTER	IOR verse side)		5. LEASE DESIGNATION	
					NM 040544	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)					· · ·	
1. OIL GAS WELL WELL			······································	<u></u> ,,,,,,,	7. UNIT AGREEMENT N	AME
WELL L' WELL 2. NAME OF OPERATOR					8. FARM OR LEASE NA	ME
Texas American Oil Corporation					Todd "26" F	ederal
3. ADDRESS OF OPERATOR					9. WELL NO.	
1012 Midla 4. LOCATION OF WELL See also space 17 1 At surface	nd <u>Savings Bld</u> (Report location clearly below.)	g Midland. To and in accordance with any	exas 79701 7 State requirements	.•	4 10, FIELD AND FOOL, Sand Dunes (Cherry Car 11. SEC., T., B., M., OE SURVEY OF ARE	IYON) Un BLK. AND
660' FNL & 1980' FEL, Sec. 26-235-31E					Sec 16, T-2	3-S. R-3
14. PERMIT NO.		ELEVATIONS (Show whether D			12. COUNTY OF PARIS	
		3446.8 GR	<u>.</u>		Eddy	New M
16.	Check Approp	riate Box To Indicate 1	Nature of Notice	, Report, or O	ther Data	
	NOTICE OF INTENTION T				ENT REPORT OF:	
TEST WATER SHUY FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	MULTIP ABANDO	DE ALTER CASING PLE COMPLETE ON* E PLANS	(Other)(Note	REATMENT R ACIDIZING Surface Ca : Report results	REPAIRING ALTERING ( ABANDONME Sing of multiple completion tion Report and Log fo	CASING
17	OP COMPLETED OPERATION	s (Clearly state all pertine	it details, and give	pertinent dates,	including estimated da	te of starting
17. DESCRIBE PROPOSED proposed work, nent to this work <u>4-13-72 to 4</u>	-,	drilled, give subsurface loca	tions and measured	and true vertical	depths for all marker	s and zones p
<u>4-13-72 to 4</u> Spudded Apr set @ 618'.	<u>-16-72</u> : il 13, 1972. D Cemented with	Drilled 12-1/4"; n 380 sx Class "	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake	20# surface o /sx and 2% C	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C	. 8-5/8"- ello Flake d casing w	20# surface o /sx and 2% Ca vith 800# befo	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w	20# surface o /sx and 2% Ca vith 800# befo	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w	20# surface of /sx and 2% Ca vith 800# befo	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befo 2EIVED 19 1972	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befo 2EIVED 19 1972	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4"; n 380 sx Class " VOC 14 hrs 4-14	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befo 2EIVED 19 1972	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5 drilling ahea	<u>-16-72</u> : il 13, 1972. E Cemented with 50 sx to pit. W ad with 7-7/8"	Drilled 12-1/4" 1 380 sx Class " OC 14 hrs 4-14 hole.	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befo	casing aCl.
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5 drilling ahea	<u>-16-72</u> : il 13, 1972. D Cemented with 50 sx to pit. W	Drilled 12-1/4" n 380 sx Class " VOC 14 hrs 4-14 hole. and correct	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befor 2EIVED 19 1972 VGICAL SURVER VEW MEXICO	casing aCl. re
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5 drilling ahea 18. I hereby critity the SIGNED	$\frac{-16-72}{11}$ il 13, 1972. E Cemented with 50 sx to pit. W d with 7-7/8"	Drilled 12-1/4" 1 380 sx Class " OC 14 hrs 4-14 hole.	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befor 2007 19 1972 19 1972 19 1972 19 1972 19 1972	casing aCl. re
4-13-72 to 4 Spudded Apr set @ 618'. Ci rculated 5 drilling ahea 18. I hereby pruity the SIGNED	<u>-16-72</u> : il 13, 1972. E Cemented with 50 sx to pit. W id with 7-7/8" it the foregoing is true a	Drilled 12-1/4" n 380 sx Class " VOC 14 hrs 4-14 hole. and correct	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befor 2EIVED 19 1972 VGICAL SURVER VEW MEXICO	casing aCl. re
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5 drilling ahea 18. I hereby pruity the SIGNED (This enforce for Fe	-16-72: il 13, 1972. D Cemented with 50 sx to pit. W 1d with 7-7/8" at the foregoing is true s 1. Man tell of State office use)	Drilled 12-1/4" n 380 sx Class " VOC 14 hrs 4-14 hole. and correct	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befor 2EIVED 19 1972 VGICAL SURVER VEW MEXICO	casing aCl. re
4-13-72 to 4 Spudded Apr set @ 618'. Circulated 5 drilling ahea 18. I hereby pruity the SIGNED (This enforce for Fe	-16-72: il 13, 1972. D Cemented with 50 sx to pit. W id with 7-7/8" at the foregoing is true a 1. Market is true to the state office use) APPBOVIL, IF ANY:	Drilled 12-1/4" n 380 sx Class " VOC 14 hrs 4-14 hole. and correct MUU TITLE	hole to 618'. C'', 1/4# C -72. Teste	. 8-5/8"- ello Flake d casing w RE( APR	20# surface of /sx and 2% Ca vith 800# befor 20 19 1972 GICAL SURVEN SELVED DATEA pr	casing aCl.