

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.O.S.	☒
LAND OFFICE	☒
OPERATOR	☒

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

0+6-NMOCD-Hobbs 1-Mr. J.A.-Midland
1-File 1-Engr. BDB
1-Foreman CK

RECEIVED BY

JUN 28 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 11-1-7

4. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☒	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name Cedar Canyon "9"
3. Address of Operator P.O. Box 730, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER P 770 FEET FROM THE South LINE AND 770 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 24-S RANGE 29-E N.M.P.M.	10. Field and Pool, or Wildcat Cedar Canyon Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 2968' DF	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

1. Pull rods and install BOP. Pull 2 3/8" tbg @ 4374'.
2. Clean 9 5/8" csg to 5300' with 2 7/8" workstring.
3. Perf the Delaware w/1 spf @ 5234, 42, 44, 46, 48, 54 and 5256', total 7 holes.
4. Set RBP @ 5300' and pkr @ 5180' and frac perfs @ 5234-56' with 250 gal 7 1/2% HCl, 14,000 gal 75% quality gelled methanol and 25,000# 12-20 sand.
5. Set RBP @ 4600' and pkr @ 4480' and frac Delaware perfs @ 4536-38', 8 holes w/250 gal 7 1/2% HCl, 14,000 gal 75% quality gelled methanol and 25,000# 12-20 sand.
6. TOH w/workstring.
7. Install 2 3/8" tbg to ± 5200' and put well on pump.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett

TITLE Area Superintendent

DATE 6/19/84

Original Signed By

Leslie A. Clements

Supervisor District II

APPROVED BY

TITLE

DATE

JUL 0 5 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 28 1984

O.C.D.
HOBBS OFFICE