

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI
(Other Instruct
verse side)

CATE*
on re

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0275360

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Drag-B

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Carlsbad, South (Morrow)-

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Gas

18, 23-S, 27-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1.

OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

Room 711 Phillips Building, Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FS & W Lines (Unit K)

14. PERMIT NO.

--

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Advise later

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Warton Drilling Company MI & RU. Spudded 17-1/2" hole at 9:30 AM, 5-25-72.
Drilled to 369'. Set 10 jts (369') 48#, H-40, ST&C, A-condition csg at 369'. Howco
cemented w/425 sx Class "H" cement w/2% CaCl₂ and 1/4# Flocele/sx. Plug to 330'
w/56 BW. Max press 300#. Circ 100 sx cement. Job completed 9:45 PM, 5-25-72.
WOC 18 hrs, tested casing w/1000# for 30 minutes, OK. WI hole w/11" bit, drilled
cement 309-69', started drilling ahead in 11" hole at 369'.

RECEIVED

JUN-5 1972

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE

Senior Reservoir Engineer

DATE

5-31-72

(This space for Federal or State office use)

TITLE

DATE

APPROVED

R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-485229

947-485