

U. S. DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR  
(Other instructi  
verse side)CATE  
OR reForm approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 030386

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SMITH FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

ROCK TANK (U&amp;L MORROW)

11. SEC., T., E., M., OR BLK. AND  
SURVEY OR AREAUNIT G, SEC. 14, T-23-S,  
R-24-E

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

1. OIL ☐ GAS ☒ OTHER  
WELL WELL

2. NAME OF OPERATOR

ADOBE OIL COMPANY

3. ADDRESS OF OPERATOR

601 GIHLS TOWERS EAST MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

2003' FNL &amp; 1836' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

38901' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON\* ☐REPAIR WELL ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT\* ☐(Other) ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

1. Set Halco E-Z Drill retainer at 8300'.  
2. Squeeze perfs from 8409-8899 with 300 sacks class H with .6% Halad 9 and 100 sacks class H with 5# No. 3 sand per sack.  
3. Drill out to retainer at 8910.  
4. Test to 1600 ps' surface pressure.  
5. Drill retainer and cement to retainer at 8980.  
6. Test to 1600 PSI surface pressure.  
7. Drill out retainer and cement to cast iron B.P. @ 9075.  
8. Test perfs to 1600 PSI surface pressure.  
9. Displace hole with 10# KCL water.  
10. Drill cast iron bridge plug and clean out hole to 10,246.  
11. Run in hole with Schlumberger and perf 1 hyperjet shot @ 10, 203, 02, 01, 10, 200, 10, 199, 98, 97, 96, 95, 94, 93, 92, 88, 87, 86, 85, 84, 81, 80, 70.  
12. Acidize with 3,000 Gal. 7.5% M.S. acid, and 30 ball seal.  
13. Flow and swab back acid.

RECEIVED

SEP 12 1975

SEP 15 1975

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

WORK TO BE COMMENCED SEPTEMBER 5, 1975.

O. C. C.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

9-5-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side