

DEPARTMENT OF THE INTERIOR (Reverse Side)
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER Dry Hole		5. LEASE DESIGNATION AND SERIAL NO. NM 0295264
2. NAME OF OPERATOR Jake L. Hamon		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 908 Vaughn Building, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 1650' FNL & 2310' FWL of Section 23, T-23-S, R-24-E, NMPM		8. FARM OR LEASE NAME Union Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3894.8' GR - 3909' K.B.		10. FIELD AND POOL, OR WILDCAT Rock Tank (Upper Morrow)
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 23, T-23-S, R-24-E NMPM
		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set Halliburton E-Z Drill Bridge Plug at 10,000' KB- and dumped 20' of cement on top of bridge plug on August 7, 1973.

Pulled 9063' of 4-1/2" casing. September 5, 1973.

Set cement plugs as follows:

Set 35 sacks @ 8850' to 8750' - Top of Strawn Lime;

Set 35 sacks @ 7300' to 7200' - Top of Lower Bone Spring Sand;

Set 35 sacks @ 5350' to 5250' - Top of Upper Bone Spring Sand;

Set 35 sacks @ 3700' to 3600' - Bone Spring Lime Section;

Set 75 sacks @ 2650' to 2450' - in and out of 8-5/8" surface casing set at 2549.07'.

Set 10 sacks in top of 8-5/8" surface casing and set permanent marker in top of well.

The above work was completed on September 5, 1973.

The USGS will be notified when location is leveled and ready for inspection.

RECEIVED
NOV 20 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Superintendent

DATE

November 19, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side