

N. M. O. C. C. COPY
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TR (Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

3. LEASE DESIGNATION AND SERIAL NO.

NM 0281482-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

El Paso Natural Gas Company ✓

FEB 19 1973

3. ADDRESS OF OPERATOR

1800 Wilco Building, Midland, Texas 79701 N. M. O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3351.5 Gr.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 29, T-23-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run 3 1/2" Tbg, perf and Acidize

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-27 - Ran 375 jts 3 1/2" tbg, set at 12,039.13, PBR stringer on bottom.

Perforated: 8 holes @ 14,410-418', 5 holes 14,492-97', 8 holes 14,564-71',
6 holes @ 14,594-99', 1 shot per foot 14,375-88', 14,396-402'.Acidized: 250 gallons mud acid + 4000 gals 7 1/2 % M S Acid & 500 SCF/bbl. Injected 50 - 7/8" Ball Sealers, displaced w/130 bbls 2% KCl w/500 SCF N₂ per bbl. AIR 6 1/2 BPM, ATP 4500-6500, ISD 5650#, 2 minute - 4950#, 20 Minutes - 3800#.

RECEIVED

FEB 16 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. Kagan

TITLE Production Clerk

DATE 2-14-73

(This space for Federal or State/office use)

APPROVED

TITLE

DATE

FEB 16 1973
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side