UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

ο.	LEASE	
	Mobil	Federal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Mobil Federal

6	IF INDIAN	ALLOTTEE OR TRIBE NAME

CHMDDV	MOTICES	AND	REPORTS	ON	WELLS
SHNDRY	NOTHER	LIVIA	REPURIS	UN	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1.	oil well		gas well		othe	er		A. A. A. A
2.	NAM	E OF C	PERA	TOR		,	JAN	
	El	Paso	Nat	ural	Gas	Co./		

3. ADDRESS OF OPERATOR

1800 Wilco Bldg. Midland, Tx. ABTESS 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 1980 FSL 1980 FEL below.)

AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

10: FIELD OR WILDCAT NAME W. Sand Dunes A Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 29, T-23-S, R-31-E :: 12. COUNTY OR PARISH 13. STATE

Eddy 14. API NO.

9. WELL NO. #1

> 0281482-A NM

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3351.5 GL

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF

FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

(other)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

SUBSEQUENT REPORT OF:

change on Form 9-330.) (NOTE: Report results of

ROSWELL, NEW MEXICO

New Mexico

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completed Operations (12-15-80 to 1-4-81)

1. Rig up pulling unit and Foamair Inc.

- Drilled and pushed Otis WB Packer to 14,650' TD. Circulated & cleaned well to TD. (14,650')
- Tested original perfs 14,375' to 14,599'. Built up to 1750 psig. 3.

Supplemental (1-5-81) - (Per phone to Mr. Jim Gillham)

- 1. Set C.I. plug @ 14,570'- cap with 1 sk. cement.
- 2. Perforate Upper Morrow interval f/ 14,028' to 14,038'.
- 3. Acidize all Morrow perfs. w/ 6000 gal, 71% MS Acid w/ 1500 SCF N2/ bbl.
- Allow well to clean up, Test and tie into sales line.

Subsurface Safety Valve: Manu. and Type None Set @ 18. I hereby certify that the foregoing is true and correct Jan. Area Engr. SIGNED (This space for Federal or State office use)

_ DATE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

U.S. GEOLÓGICAL SURVEY ROSWELL, NEW MEXICO,