| O+5 - USGS - P.O. Box 1857 Roswell, NM 3201 | 1 - Engr JIM 1 - foreman - CK | l - WIO's - File |
|---|---|--|
| | FM OIL COME, COM Drawle Ho | MISSION . |
| Form 9–331 Dec. 1973 | Artonia, Af 092 | 10 Form Approved. Budget Bureau No. 42–R1424 |
| UNITED STATES | - | 5. LEASE |
| DEPARTMENT OF THE INTERIOR C/SF GEOLOGICAL SURVEY | | NM-12841 6. IF INDIAN, ALLOTTEE OR TRIBERAMEVED |
| GEOLOGICAL SUR | V C, 1 | |
| SUNDRY NOTICES AND REPO (Do not use this form for proposals to drill or to dec reservoir, Use Form 9-331-C for such proposals.) | 7. UNIT AGREEMENT NAME MAR - 8 1982 Cedar Canyon 10 | |
| 1. oil gas well other | | 8. FARM OR LEASE NAME Cedar Canyon 10 9. WELL NO. ARTESIA, OFFICE |
| 2. NAME OF OPERATOR | | 1 |
| Getty Oil Company / 3. ADDRESS OF OPERATOR | | 10. FIELD OR WILDCAT NAME Like Althor Cedar Canyon - Morrow Gas |
| P.O. Box 730 Hobbs, NM 88240 | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) | | AREA Sec. 10, T-24S, R-29E |
| AT SURFACE: Unit ltr. F, 2180 FNL & 1980' FWL AT TOP PROD. INTERVAL: | | 12. COUNTY OR PARISH 13. STATE |
| AT TOTAL DEPTH: | | Eddy NM |
| 16. CHECK APPROPRIATE BOX TO INDICA | TE NATURE OF NOTICE, | |
| REPORT, OR OTHER DATA | | 15. ELEVATIONS (SHOW DF, KDB, AND WD) 2941' G.L. |
| REQUEST FOR APPROVAL TO: SUBS | SEQUENT REPORT OF: | |
| FRACTURE TREAT | | इहार्श्वानी |
| SHOOT OR ACIDIZE | | (NOTE: Report results of multiple completion or zone |
| PULL OR ALTER CASING MULTIPLE COMPLETE | | 0 0 10 00 11 bl |
| CHANGE ZONES ABANDON* X | | OIL & GAS |
| (other) | U.S. G | EOLOGICAL SURVEY VELL, NEW MEXICO |
| 17. DESCRIBE PROPOSED OR COMPLETED including estimated date of starting any measured and true vertical depths for all | OPERATIONS (Clearly state proposed work, if well is de- | te all pertinent details, and give pertinent dates, |
| l. Rig up pulling unit a | nd install BOP. | |
| 2. Run cement retainer o | n tubing and set at | t <u>+</u> 3450'. |
| Cement with 150 sxs c Displace hole with br | | ol. |
| 5. Perforate 2 holes at | 710', run cement re | etainer and set at + 600'. |
| 6. Cement with 300 sxs c Leave approximately 1 | lass "C" attempting 00' plug in 9 5/8" | g to circulate out $\overline{13}$ 3/8" bradenhead. casing at 600' - 700'. |
| Spot 25 sxs cement pl | ug at surface. | |
| Cut off wellhead and Clean location. | install dry hole ma | arker. |
| | | |
| Subsurface Safety Valve: Manu. and Type | | Set @ Ft. |
| 18. I hereby certify that the foregoing is true | , | |
| SIGNED Loral Mainner | Area Super: | intendent February , 1982 |
| ATTROVE | his space for Federal or State of | fice use) |
| APPROVED BOTIS. Sgd.) PETER W. CHE | TERTE | DATE |
| conditions of Approval, if any: | | |
| FOR | | · · |
| JAMES A. GILLHAN | N See Instructions on Reverse | Side |