

SORENSEN "COM" NO. 1
1980' FN&EL Section 14, T-23-S, R-26-E
Eddy County, New Mexico

Attachment - Form C-103

17. 2-11-77: Pumped 35 sx Class "E" cement plug @ 11,620' above Morrow perfs @ 11,732-11,778'. Pumped 45 sx Class "E" cement plug @ 11,217' above Strawn and Atoka perfs @ 11,222-10,837',
- 2-15-77: Ran freepoint, cut 5½" casing w/McCullough Chemical cutter @ 10,130', pulled & laid down 5½" casing,
- 2-22-77: Pumped 35 sx Class "C" cement plug down 2-7/8" tubing @ 10,180', 50' inside and 50' outside, 5½" casing stub @ 10,130',
- 2-25-77: Mixed and pumped 50 sx salt gel mud, circulated hole. Pumped 35 sx Class "E" cement plug @ 8,776-8,676', Top of Wolfcamp,
- 2-26-77: Pumped 35 sx Class "H" cement plug 6,477-6,377', Top of Bone Springs. Pumped 35 sx Class "H" cement plug w/2% Calcium Chloride @ 5,375-5,275', base of 9-5/8" casing set @ 5,330',
- 2-28-77: Set Baker Model N 9-5/8" C.I.B.P. @ 2,800'. Bailer dumped 2 sx cement on top of plug, PBTD 2,795'.

Report on Delaware recompletion operations to follow.