

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Belco Petr Corp.		Lease Union Mead Com		Well # 3	
Location of Well	Unit 198054e	Section 5	Township 22	Range 27	County Eddy
Drilling Contractor	McVay Drilling Co.		Type of Equipment Rotary to start 12-29-72		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2 20	+3 3/8 16			350	350 circ.
17 1/4 14 3/4	10 3/4	32.75 + 40.50		1950	circ.
9 1/2	7 5/8"	26.40		8800	250
Casing Data:	5 1/2	20		11650	210

Surface 56 joints of 10 3/4 inch 32-40 # Grade API New H-40, K-55
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 14 3/4" Size of Casing 10 3/4" Sacks cement required 1150
Type of Shoe used Cush Float collar used Insert Btm 3 jts welded Thread Lock
TD of hole 1850 Set 1833 Feet of 10 3/4 inch 32-40 # Grade API New
New-used csg. @ 1833 with 150 sacks neat cement around shoe Class C 2% CC 14.8
+ 1000 sax Halco Lite additives 4 Floc-1 2% CC 13.0

Plug down @ 4:45 (AM) (PM) Date 1-9-72

Cement circulated No No. of Sacks None

Cemented by Halliburton Witnessed by L. J. Mcmanis

Temp. Survey ran @ 11:00 (AM) (PM) Date 1-9-72 top cement @ 475

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Surface 20" hole 8 ft to 16" 55' H-40 TD 340 set 335 RD

Surface Shoe - Thread Lock, 42 5/8" Class C 2% CC Circ. 100/sx

Plug down 2:00 P.M. 1-1-72

Intermediate One Inched 5 Tagged Cement at 465' - Cemented With
350/sx Class C 2% CC 14.0 # Cement Circ. to Surface.

12-31-72