

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 26 1972

30-015-20789

Form C-101
Revised 11-65

5A. Indicate Type of Lease
STATE ☐ FEE ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
Howard Hemler

9. Well No.
1

10. Field and Pool, or Wildcat
Carlsbad, South

12. County
Eddy

19. Proposed Depth
11,800'

19A. Formation
Strawn & Morrow

20. Rotary or C.T.
Rotary

21. Elevation (Show whether DP, RT, etc.)
3168 GR

21A. Kind & Status Plug. Bond
Blanket

21B. Drilling Contractor
Moranco

22. Approx. Date Work will start
12/26/72

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work
ARTESIAN ☐ DRILL ☒ DEEPEN ☐ PLUG BACK ☐

b. Type of Well
OIL WELL ☐ GAS WELL ☒ OTHER ☐ SINGLE ZONE ☐ MULTIPLE ZONE ☐

2. Name of Operator
Brunson and McKnight

3. Address of Operator
Box 297, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER L LOCATED 1980 FEET FROM THE South LINE
AND 660 FEET FROM THE West LINE OF SEC. 29 TWP. 22 - S RGE. 27 - E NMPM

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2"	13 3/8"	43#	350	375	surface
12 1/4"	9 5/8"	36# & 40#	5,400	1750	1500
7 7/8"	5 1/2"	17#	11,800	400	9800

* No allowable may be assigned until a standard 320 acre unit is dedicated or the 1500' approved.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,
EXPIRES 3-26-72

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Byron McKnight Title Agent Date 12/22/72
(This space for State Use)

APPROVED BY W. A. Grissett TITLE STATE OIL CONSERVATION ASPECTOR DATE DEC 26 1972

CONDITIONS OF APPROVAL, IF ANY: *
Adequate blowout prevention
equipment to be used
Cement must be circulated to
surface behind 13 3/8" casing