		N. M. O. C. C	COPY			Bape	F GSF
orm-2-334 May 1963)	DEPART	U ED STATES	NTERIOR	SUBMIT IN TRI (Other instruction verse side)	· · · ·	Form approve	d. 1 No. 42 (R1424
CD0 not use	UNDRY NO this form for prop Use "APPLIO	TICES AND REPC	RTS ON	A different reservoir.	D 6.	IF INDIAN, ALLOTTEE	OR TRIBE NAME
				26 1973		UNIT AGREEMENT NAM	(E
WELL WE						IMES Ranch Ur	-
	oleum Corpo	pration Process	A.	TESIA, DEFICE		umes Ranch Ur	
	Building,	Midland, Texas	79701			WELL NO.	
See also space 17 At surface	(Report location (below.)	clearly and in accordance v	with any State	equirements.*	IE DUn	designated	WILDCAT
2180' FSL County, Ne	& 330' FWL w Mexico	of Section 6, T-	23-S, R-3	DCT26	1973 Se	prow Gas spec. T. R. M. OR BL subury or ARFA ction 6, 28-S, R-31-E	
4. PERMIT NO.		15. ELEVATIONS (Show w	hether DF, RT, GR	etc.) coi 061	CAL SUN	COUNTY OF PARISH	13. STATE
Dated 5-4-	73	3296' GR		etc.) OCT20	<u>, i Éd</u>	dy	New Mexic
6.	Check A	Appropriate Box To Ind	icate Nature			Data	
	NOTICE OF INT	INTION TO :		1	SUBSEQUENT	REPORT OF:	
TEST WATER SH		PULL CR ALTER CASING	_	WATER SHUT-OFF		REPAIRING WI	EL.I.
FRACTURE TREAT SHOUT OR ACIDIZ		MULTIPLE COMPLETE		FRACTURE TREATMENT SHOOTING OR ACIDIZID	· · · · ·	ALTERING CAS	
on on Acidi		CHANGE PLANS		(Other) Set Li	iner & C	omplete	XX
REPAIR WELL					mogulto of m	ultiple completion of	n Well
(Other) 7. DESCRIBE PROPOSE proposed work nent to this wo Drilled 6 line set a "H" cement	rk.)* 1/2" hole t s a liner a with 5# KC	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR-	n 73 join ulated 5 2 per sac	ls, and give pertinent d measured and true ts (2898') of hours and cen k added. Plu	Recompletion t dates, inclu vertical dep E 5 1/2" Mented w	Report and Log form ding estimated date this for all markers , 20#, N-80, ith 300 sack	of starting an and zones pert ABC Flus s of Clas
(Other) 7. DESCRIBE FROMOSE proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered	<pre>http://www.name.of/ 1/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of rop. Unsea bridge plug 1 Morrow Zop</pre>	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and 4 1/2" bit and an cement bond 14 2'-2C' with 2 jet through annulus 0-114'. Flowed 14 mmediately above ulated hole. Spo 912-920'. Attempout acid. Instate plug. Set retro oka Zone with 750 CO2. During first ted packer and ret had failed as hat ne. POH with RB	n 73 join ulated 5 2 per sac drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zo: packer a otted 150 pted to p lled B.0. rievable 1 00 gallon st part of etrieved 1 ad Otis Ri	Completion or I ls. and give pertinent dd measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow Z he to clean u t 13,750'. C D gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr oridge plug f d packer at 1	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w 1g down t out of top of head an top of head an top same. Dpened s 7 1/2% Atoka t ubing at 13,00 er with peatment from a de 3,750'.	Report and Log form dung estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packet 6500# sand, , there was epth of 14,1 Fracture to	ABC Flus and zones perti- s of Clas , 8-10-73 ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment
Other) 7. DESCRIBE PROPOSE proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS	<pre>http://www.nstanter l/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of for rop. Unsea pridge plug d Morrow Zon d treating p Acid. Atoka</pre>	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and 4 1/2" bit and 10 an cement bond 10 2'-2C' with 2 jet through annulus 0-114'. Flowed 10 mmediately above ulated hole. Spo 912-920'. Attempout acid. Instal e plug. Set retr oka Zone with 750 CO ₂ . During first ted packer and ret	n 73 join ulated 5 2 per sac drilled 5 drilled 5 drilled c og. Inst t shots p . Perfor Morrow Zos packer a otted 150 pted to p lled B.0. rievable 1 00 gallons st part of etrieved 1 ad Otis RI P and pac '. Acidis espond. 1	Completion or I ls. and give pertinent dd measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. Co gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr oridge plug f d packer at 1 ker. Ran new	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w lg down t op of head an t otis R Cone fro pened s 7 1/2% Atoka t ubing at 13,00 er with peatment from a de 3,750'. RBP and foration Atoka Zo	Report and Log form dung estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packet 6500# sand, , there was epth of 14,1 Fracture ti d packer. So	ABC Flus s of Clas s of Clas s of Clas ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w
Other) 7. DESCRIBE PROPOSE proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS	<pre>http://www.nstanter l/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of for rop. Unsea pridge plug d Morrow Zon d treating p Acid. Atoka</pre>	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and an cement bond 1 2'-2C' with 2 je through annulus 0-114'. Flowed 1 mmediately above ulated hole. Spe 912-920'. Attemp out acid. Insta e plug. Set retr oka Zone with 756 CO ₂ . During firs ted packer and re had failed as have ne. POH with RBI packer at 12,787 a Zone did not re	n 73 join ulated 5 2 per sac drilled 5 drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zoi packer a otted 150 pted to p lled B.0. rievable 1 00 gallon st part of etrieved 1 ad Otis Ri P and pac '. Acidi: espond. 1	Completion or I ls. and give pertinent dd measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. C D gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr pridge plug f i packer at 1 ker. Ran new zed Atoka per Reperforated	Recompletion dates, inclu- vertical dep 5 1/2" mented w 1g down c out of top of head an c Otis R Cone fro 1p same. Dpened s 7 1/2% 0 Atoka 1 tubing 1 13,000 er with beatment rom a do 3,750'. 7 RBP and foration Atoka Za	Report and Log form ding estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packe 6500# sand, , there was epth of 14,1 Fracture t: d packer. So ns with 1500 one from 12,0 ONTINUED NEX:	ABC Flus and zones perti- ABC Flus s of Clas , 8-10-73 ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w T-PAGE)
(Other) 7. DESCRIBE FROMOSSI proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS 2	rk.). 1/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated of vable bridge to treat Ato 20 tons of rop. Unsea bridge plug d Morrow Zon d treating p Acid. Atok	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and an cement bond 10 2'-2C' with 2 jet through annulus 0-114'. Flowed mmediately above ulated hole. Spo 912-920'. Attem out acid. Instal e plug. Set retr oka Zone with 750 CO ₂ . During firs ted packer and re had failed as have ne. POH with RBI packer at 12,787 a Zone did not ret is true and correct Glenn Cope TITL	n 73 join ulated 5 2 per sac drilled 5 drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zoi packer a otted 150 pted to p lled B.0. rievable 1 00 gallon st part of etrieved 1 ad Otis Ri P and pac '. Acidi: espond. 1	Completion or I ls. and give pertinent dd measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. C D gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr pridge plug f i packer at 1 ker. Ran new zed Atoka per Reperforated	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w 1g down c out of top of head an c Otis R Cone fro op same. Opened s 7 1/2% o Atoka 1 tubing t 13,000 er with beatment foration Atoka Za (Cone Cone	Report and Log form ding estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packe 6500# sand, , there was epth of 14,1 Fracture t: d packer. So ns with 1500 one from 12,0 ONTINUED NEX:	ABC Flus and zones perti- ABC Flus s of Clas , 8-10-73 ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w T-PAGE)
(Other) 7. DESCRIBE FROMOSSI proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS 2	rk.)* 1/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of rop. Unsea bridge plug 1 Morrow Zon d treating p Acid. Atoka that the foregoing	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and 4 1/2" bit and an cement bond 10 2'-2C' with 2 jet through annulus 0-114'. Flowed mmediately above ulated hole. Spo 912-920'. Attemp out acid. Insta e plug. Set retr oka Zone with 750 CO ₂ . During firs ted packer and re had failed as have ne. POH with RBI packer at 12,787 a Zone did not re Is true and correct Glenn Cope TITL fice use	n 73 join ulated 5 2 per sac drilled 5 drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zoi packer a otted 150 pted to p lled B.0. rievable 1 00 gallon st part of etrieved 1 ad Otis Ri P and pac '. Acidi: espond. 1	Completion or I ls. and give pertinent dd measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. CD gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr oridge plug f i packer at 1 ker. Ran new zed Atoka per Reperforated	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w 1g down c out of top of head an c Otis R Zone fro 1p same. Dpened s 7 1/2% Atoka 2 1 tubing 1 13,00 er with beatment From a de 3,750'. (Contemporation Atoka 2 (Contemporation) (Con	Report and Log form ding estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packe 6500# sand, , there was epth of 14,1 Fracture t: d packer. So ns with 1500 one from 12,0 ONTINUED NEX:	ABC Flus and zones perti- s of Clas , 8-10-73 ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w T_PAGE)- 3/73
(Other) 7. DESCRIBE FROMOSS proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS 8. I hereby certify SIGNED (This space for ABPROVED BY	rk.)* 1/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of rop. Unsea bridge plug 1 Morrow Zon d treating p Acid. Atoka that the foregoing	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and 4 1/2" bit and an cement bond 14 2'-2C' with 2 jet through annulus 0-114'. Flowed 14 mmediately above ulated hole. Spo 912-920'. Attemp out acid. Instate e plug. Set retro oka Zone with 750 CO2. During first ted packer and ret had failed as hat ne. POH with RBH packer at 12,787 a Zone did not ret 1s true and correct Glenn Cope TITL meter use	n 73 join ulated 5 2 per sac drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zo: packer a otted 150 pted to p led 8.0. rievable 1 00 gallons st part of etrieved 1 ad Otis Ri P and pac '. Acidi: espond. 1	Completion or I Is and give pertinent do measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. CD gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr oridge plug f d packer at 1 ker. Ran new zed Atoka per Reperforated	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w 1g down c out of top of head an c Otis R Zone fro 1p same. Dpened s 7 1/2% Atoka 2 1 tubing 1 13,00 er with beatment From a de 3,750'. (Contemporation Atoka 2 (Contemporation) (Con	Report and Log form dung estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packer 6500# sand, , there was epth of 14,1 Fracture t: d packer. So ns with 1500 one from 12, ONTINUED NEX' DATE10/22	ABC Flus and zones perti- s of Clas , 8-10-73 ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w T_PAGE) 3/73
(Other) 7. DESCRIBE FROMOSS proposed work nent to this wo Drilled 6 line set a "H" cement W.O.C. 18 of liner h to bottom. Atoka Zone Brought in 14,072-88' file in on above pack perforation success. and retrie Rigged up beads and pressure di trievable 1 had entered 13,774' and 7 1/2% MS 8. I hereby certify SIGNED (This space for ABPROVED BY	rk.)* 1/2" hole t s a liner a with 5# KC hours. Ran anger. Ran POH and r from 12,91 Atoka Zone ; and 14,11 -off tool i er and circ ns from 12, Circulated vable bridg to treat Ato 20 tons of rop. Unsea bridge plug 1 Morrow Zon d treating p Acid. Atoka that the foregoing	o 14,380' and rat t 14,380'. Circ L plus 1.5% CFR- 6 1/2" bit and 4 1/2" bit and an cement bond 14 2'-2C' with 2 jet through annulus 0-114'. Flowed 14 mmediately above ulated hole. Spo 912-920'. Attemp out acid. Instate e plug. Set retro oka Zone with 750 CO2. During first ted packer and ret had failed as hat ne. POH with RBH packer at 12,787 a Zone did not ret 1s true and correct Glenn Cope TITL meter use	n 73 join ulated 5 2 per sac drilled 5 drilled 5 drilled c og. Inst. t shots p . Perfor Morrow Zo: packer a otted 150 pted to p lied B.0. rievable 1 00 gallon st part of etrieved 1 ad Otis Ri P and pack '. Acidi: espond. 1	Completion or I Is and give pertinent do measured and true ts (2898') of hours and cen k added. Plu 00' of cement ement out of alled tubing er foot. Set ated Morrow 2 he to clean u t 13,750'. CD gallons of ump acid into P. and pulled oridge plug a s gelled wate f fracture tr oridge plug f d packer at 1 ker. Ran new zed Atoka per Reperforated	Recompletion t dates, inclu- vertical dep E 5 1/2" mented w 1g down c out of top of head an c Otis R Zone fro 1p same. Dpened s 7 1/2% Atoka 2 1 tubing 1 13,00 er with beatment From a de 3,750'. (Contemporation Atoka 2 (Contemporation) (Con	Report and Log form dung estimated date iths for all markers , 20#, N-80, ith 300 sack at 5:45 p.m. 7 5/8" casi liner and ci d B.O.P.'s. H packer at m 13,865-79' Set tubing liding sleev MS Acid acro perforations . Ran treat 0' and packer 6500# sand, , there was epth of 14,1 Fracture t: d packer. So ns with 1500 one from 12, ONTINUED NEX' DATE10/22	ABC Flus s of Clas s of Clas s of Clas ng to top rculated Perforat 13,750'. ; 13,888- plug in e immedia ss Atoka without ing packe r at 12,8 1000# gla a sudden 20'. Re- reatment et RBP at gallons 912-20' w T PAGE) 3/73

• ł