DST Description Continued From USGS Form 9-330 October 22, 1973

-

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Atoka Carbonate	13000'	13,048'	<pre>Ran 3000' water blanket. Opened for 10 minute preflow with weak blow. Shut in for 90 minute ISIP. Opened for 90" final flow period with weak to fiar blow. Shut in for 180" final shut in pressure. PRESSURES: 10 minute preflow - 2412# - 2773# 90 minute I.S.I.P 5427# 90 minute F.F 3515# 180 minute F.S.I.P 5183# IHP - 8945# FHP - 8945# BHT - 188°F. Reversed out 6138' gas-cut mud and 3000' water blanket. Sample chamber recovery 7.13 cubic feet gas at 2400# - no fluid.</pre>
Strawn, Atoka Sand, & Atoka Carbonate	12,732' 13,079' RECEIVED OBT 26 1973 U. S. GEOLO-IGAL SUR U. S. GEOLO-IGAL SUR		Ran 3000' water blanket. Opened for 10 minute preflow with strong blow. Shut in for 90 minute ISIP. Opened for 55 minute flow period with GTS in 40" and water blanket to surface in 45". Surface flowing pressure was 100# on a 1" adjustable choke. Shut in for one hour and 55 minute second shut in period. Opened tool for 120 minute final flow period with GTS immediately. Flow pressure stabilized at 500" on a 1/2" P.C. Flow rate approximately 3,400 MCFPD. Shut in for 2 hour FSIP. <u>PRESSURES</u> :
		U.S. GOOLA CALL BOOM	IHP - 9117# 10" Preflow - 1945# 90" ISIP - 5166# 55" IFP - 2391# 150" SI - 5146# 120" FFP - 1276# 120" FSIP - 5126# FHP - 9117# Temp. - 192°F.

7