				. r. in
	-		Ē.	CIST
			್ರ., V ಎ. ಎಂ ಎಂ	
	UNITE	D STATES	1 S. 🔅 🗍	FORM APPROVED
Form 3160-5 (June 1990)		UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		Budget Bureau No. 1004-0135 Expires: March 31, 1993
,				5. Lease Designation and Serial No.
				NM-93178
Do not use this fo U	rm for proposals to drill	ND REPORTS ON WELL or to deepen or reentry to PERMIT—" for such propo	a different reservoir,	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE				7. If Unit or CA, Agreement Designation
1. Type of Well				
Oil X Gas Other				8. Well Name and No.
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471)				Rabbit ASR Federal #1 9. API Well No.
3. Address and Telephone No.				30-015-20823
105 South 4th St., Artesia, NM 88210				10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Crooked Creek Morrow
1780' FNL &	1980' FEL of Section	on 34-T23S-R24E (Un	it G, SWNE)	11. County or Parish, State
				Eddy Co., NM
		TO INDICATE NATURE	OF NOTICE BEPO	
TYPE OF	SUBMISSION		TYPE OF ACTION	· · · · · · · · · · · · · · · · · · ·
Notice o	of Intent	Abandonment		Change of Plans
[27]	-	Recompletion		New Construction
X Subsequ	ent Report	Casing Repair		Non-Routine Fracturing Water Shut-Off
Final Al	bandonment Notice	Altering Casing		Conversion to Injection
		X Other Perfo	orate & acidize	Dispose Water
				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
		ertinent details, and give pertinent dates depths for all markers and zones pertin		ng any proposed work. If well is directionally drilled,
-		and nippled up tubin	•	
				ested to 4000 psi, OK.
				05'. Ran CBL/GR/CCL logs.
				scraper and tubing to 9820'. n control HCL acid. TOOH
	0	8		B" casing guns and perf-
				sing guns and rigged down
				ested. Swabbed. Shut
well in.				
				con control HCL acid with th 3300 scf/bbl N2. Flowed
	Shut well in.	JI NZ ANG DALI SEAL	ers. rrushed wrt	th 5500 sci/bbi Nz. Flowed
		owed down. Swabbed	. Released packe	er. TOOH with tubing and
packer. Rig	gged up wireline.	TIH with CIBP and s	et CIBP at 9735'.	. Capped CIBP with 35' of
				52 .38" holes (4 SPF -
				th packer and tubing. Set
		2000 psi, OK. Swab 9658-9670' with 10		ron control HCL acid with
	foregoing is true and correct			NUED ON NEXT PAGE:
	stur lin	Tile Operation	s Technician	Date Sept. 23, 1998
Signed(A)			CEPTED FOR REGOR	
ť	or only office user	AU T	VIJ THUT WITH	
Approved by Conditions of approval,	if any:	Title	SEP 2 9 1998	Date
	((DRIG. SGD.) GARY GOL	IRLEY	
Title 18 U.S.C. Section 100	1, makes it a crime for any person kn	owingly and willfully to make to any	epartment or rate boy of the Unite	ed States any false, fictitious or fraudulent statements
or representations as to any	matter within its jurisdiction.			