This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Castile _____ 633
T. Lamar Shale _____ 1770
B. Lamar Limestone 1805
T. Delaware Sand _____ 1915
T. Bone Springs _____
T. Lime _____ 5224
T. First Bone Spring _____
T. Sand _____ 6157
T. Second Bone Spring _____
T. Sand _____ 6588
T. Third Bone Springs _____
T. Sand _____ 8213
T. Wolfcamp _____ 8637
T. Canyon _____ 10050
T. Strawn _____ 10210
T. Lusk _____ 10404
T. Atoka _____ 10520

T. Morrow Lime _____ 10811
T. Morrow Sand _____ 11413
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Granite _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Qtzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	633	633	Undifferentiated				
633	1137	1770	Castile				
1770	35	1805	Lamar Shale				
1805	110	1915	Lamar Limestone				
1915	3309	5224	Delaware Mountain Group				
5224	3413	8637	Bone Springs				
8637	1413	10050	Wolfcamp				
10050	160	10210	Canyon				
10210	194	10404	Strawn				
10404	116	10520	Lusk				
10520	291	10811	Atoka				
10811	602	11413	Morrow Lime				
11413	587	12000	T.D. Morrow Sand				
		12000	T.D				