

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDAY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

RECEIVED

1. oil well ☐ gas well ☒ other ☐ MAY 12 1978
2. NAME OF OPERATOR
Mobil Oil Corporation
3. ADDRESS OF OPERATOR
3 One-way Plaza Suite 800, Houston, TX 77046
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)
AT SURFACE: 660' FSL & 1980' FWL of Sec. 13,
AT TOP ROD. INTERVAL: T-23-S, R-26-E
AT TOTAL DEPTH:
15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☒
- REPAIR WELL ☐
- PULL OR ADD Casing ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONE ☐
- ABANDON* ☐
- (other) ☐

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 15 1978

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measurements and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Move in and rig up trucks to Morrow zone.
- 2) Acidize zone w/5000 gallons foamed acid at 6-8 BPM if pressure allows. (Do not exceed 5,000 psi). The acid mix is formed by adding 55% by volume Nitrogen and 45% HCl acid mixture. The acid mixture contains clay stabilizer as well as necessary foaming additives. Nitrogen volume will range from 3000 SCF/min to 6000 SCF/min depending on the exact bottom hole pressure encountered.
- 3) Flow well back as soon as possible after completion of the treatment into a pit.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. W. De Bore

TITLE

Authorized Agent

DATE

5/9/78

APPROVED BY

J. H. Lara

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

TITLE

MAY 16 1978

CONDITION OF APPROVAL, IF ANY: