

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-027994-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "NM" COM

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Carlsbad A. Atoka &

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 13, T-23-S, R-26-E

1.

OIL ☐ GAS ☒ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

Mobil Oil Corporation

SEP 26 1973

3. ADDRESS OF OPERATOR

Box 633, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FML & 1980' FML, Section 13, T-23-S, R-26-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3243.5

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing Test & Cement Job

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

FEDERAL "NM" COMM #1

9/19

12,050 TD, WOC 7" liner, ran 152 jts 6659' 7" OD 26.0# S-95 LT&C liner w/ BWS Type C 6-slip liner hanger on 4 1/2 DP to 12,048, landing collar @ 11,901, top of liner @ 5389, Howco cmtd liner w/ 1280x TILW cmt + 250x Class H Neat cmt, under displ cmt 58 bbls, DPP 4800, job compl @ 8:45 p.m. 9/18/73, POH w/ liner setting tool.

9/20

FEDERAL "NM" COMM #1, 12,050 TD.

Ran 8-3/4 bit to top of liner @ 5389, no cmt on top of liner, POH w/ bit, ran 9-5/8 RTTS pkr on 4 1/2 DP to 5089, Howco sqzd top of liner w/ 300x TILW containing 1/4# Flocelex + 300x Class C Neat cmt, DPP 900, job compl @ 6:30 p.m. 9/19/73, WOC, 18 hrs.

FEDERAL "NM" COMM #1, 12,050 TD.

9/21

Ran 8-3/4 bit on DC's and DP, drill cmt in 9-5/8 csg from 5307-5389, top of 7" liner, circ clean, displ to fr wtr, test csg & liner top w/ 2000#/30 min/0.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Authorized Agent

(This space for Federal or State office use)

TITLE

DATE

APPROVED

SEP 25 1973

H. L. BECKMAN
ACTING DISTRICT ENGINEERRECEIVED
SEP 25 1973
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO
DATE 9/21/73

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection, looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1964-O-695329

847-831

