

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI  
(Other instructive  
verse side)DATE  
on re-Copy to  
Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 0475051	
2. NAME OF OPERATOR Pennzoil Company.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Drawer 1828 - Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1750' FSL & 1650' FWL of Sec. 22, T-24-S, R-26-E		8. FARM OR LEASE NAME Allied -B-	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3338 K.B.		10. FIELD AND POOL, OR WILDCAT White City Penn (Morrow)	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, T-24-S, R-26-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE N. M.	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

## SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well was plugged and abandoned. - See Form 9-331 dated 8-20-73 and approved 4-26-74.

PROPOSAL: Re-enter and recover 9 5/8" casing.

1. Drill out 20 sack cement plug in surface of 9 5/8" casing.
2. Run Free Point and shoot off 9 5/8" casing (estimated free @ 1,250').
3. Spot a 75 sack cement plug on top of 9 5/8" casing stub.
4. Spot 75 sack cement plug from 385' to 285'
5. Spot 20 sack cement plug in top of 13 3/8" casing & install permanent marker.
6. Clean and level location.

RECEIVED

OCT 23 1974

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNATURE C. Raney TITLE Petroleum Engineer DATE 10-22-74

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

OCT 23 1974  
K. L. BEEKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side