N. M. O. C. C. COPY

·····	GEOLOGICAL SURVEY		5. LEASE DESIGNATION AND SERIAL NO NM.0419982A
	OTICES AND REPORTS roposals to drill or to deepen or plug LICATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE OR TRIBE NAN
			7. UNIT AGREEMENT NAME
WALL WELL OTHE	B Dry		Badger Unit
2. NAME OF OPERATOR		AUG 0 0 1971	8. FARM OR LEASE NAME
<u>Clayton W. Willia</u> 3. ALDRESS OF OPERATOR	ems, Jr.		Federal 9. WELL NO.
One Spring Drive	Font Stoolston To		1
 4. LECATION OF WELL (Report location See also space 17 below.) 	Fort Stockton, Te	y State requirements. • OFFICE	10. FIELD AND POOL, OR WILDCAT
At surface			Wildcat
1980' FSL & 1980' FWL Sec. 15, T-22-S, R-31-E		2-S, R-31-E	11. SEC., T., R., M., OR BLK. AND SUBVEY OR ABEA
			Sec.15, T-22-S,
14. PERMIT NO.	15. ELEVATIONS (Show whether D	DF, RT, GR, etc.)	$\frac{R-31-F}{12. \text{ COUNTY OB PARISH} 13. \text{ STATE}}$
14-08-0001-12400			Eddy N.M.
			5
		Nature of Notice, Report, or C	
NOTICE OF IN	·	SUBSEQU	ENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE X	SHOOTING OR ACIDIZING	ALTERING CASING
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		Completion or Recomple	of multiple completion on Well etion Report and Log form.) including estimated date of starting a
Duppede to Dive (
and structural po approval was obta in the following	osition does not wa lined from Mr. Jame manner:	arrant further dril es A. Knauf, 9-16-7	'3, to plug well
and structural po approval was obta in the following 200' Cement F	osition does not wa lined from Mr. Jame manner: Plug from 14,275' t	arrant further dril es A. Knauf, 9-16-7 co 14,075' in 8½" o	ling. Verbal 3, to plug well
and structural po approval was obta in the following 200' Cement P 100' Cement P	osition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t	arrant further dril es A. Knauf, 9-16-7 cc 14,075' in 8½" c cc 12,840' in 8½" c	ling. Verbal '3, to plug well open hole. open hole.
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P	osition does not wa lined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t	arrant further dril es A. Knauf, 9-16-7 to 14,075' in 8½" o to 12,840' in 8½" o to 11,900' in 8½" o	ling. Verbal 3, to plug well open hole. open hole. open hole & 9-5/8"ca
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F Cut off 9-5/8	osition does not wa manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to " OD Casing © appr	arrant further dril es A. Knauf, 9-16-7 to 14,075' in 8½" o to 12,840' in 8½" o to 11,900' in 8½" o to 4,200' in 9-5/8" poximately 3600' an	ling. Verbal 3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same.
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F Cut off 9-5/8	osition does not wa manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to " OD Casing © appr	arrant further dril es A. Knauf, 9-16-7 to 14,075' in 8½" o to 12,840' in 8½" o to 11,900' in 8½" o to 4,200' in 9-5/8" poximately 3600' an	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F Cut off 9-5/8 100' Cement F	osition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from approxima	arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" o to 12,840' in 8½" o to 11,900' in 8½" o 0 4,200' in 9-5/8" roximately 3600' an ately 3650' to 3550	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing & 13-3/8" casing.
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F	osition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from approxima Plug from 850' to 7	arrant further dril as A. Knauf, $9-16-7$ to 14,075' in $8\frac{1}{2}$ " of to 12,840' in $8\frac{1}{2}$ " of to 11,900' in $8\frac{1}{2}$ " of 4,200' in $9-5/8$ " coximately 3600' an ately 3650' to 3550 750' in 13-3/8" OD	<pre>ling. Verbal '3, to plug well '9, to plug well '9, to plug well '9, hole. '0, hole & 9-5/8"ca '0, casing. '0, in 9-5/8" casing '0, 13-3/8" casing. '0, casing.'*</pre>
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P 100' Cement P 100' Cement P 100' Cement P 50' Cement P	Sition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su	arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" o to 12,840' in 8½" o to 11,900' in 8½" o to 4,200' in 9-5/8" poximately 3600' an ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" O	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing. & 13-3/8" casing. D casing.
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P 100' Cement P 100' Cement P 100' Cement P 50' Cement P	Sition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su	arrant further dril es A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" poximately 3600' an ately 3650' to 3550 250' in 13-3/8" OD arface in 13-3/8" OD to final; inspector	<pre>ling. Verbal '3, to plug well '9, to plug well '9, to plug well '9, to plug well '9, to plug \$ 9-5/8"ca Casing. '10, 10, 10, 10, 10, 10, 10, 10, 10, 10,</pre>
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P 100' Cement P 100' Cement P 100' Cement P 50' Cement P	Sition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su	arrant further dril es A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" poximately 3600' an ately 3650' to 3550 250' in 13-3/8" OD arface in 13-3/8" OD to final; inspector	<pre>ling. Verbal '3, to plug well '9, to plug well '9, to plug well '9, to plug well '9, to plug \$ 9-5/8"ca Casing. '10, 10, 10, 10, 10, 10, 10, 10, 10, 10,</pre>
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P 100' Cement P 100' Cement P 100' Cement P 50' Cement P	Sition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su	arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' an ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD to final inspector	ling. Verbal 3, to plug well pen hole. pen hole & 9-5/8"ca Casing. d pull same. in 9-5/8" casing. & 13-3/8" casing. casing. D casing. AFEOn as 21974
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F Well site to possible.	position does not wa manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su be conditioned for	Arrant further dril as A. Knauf, 9-16-7 to 12,840' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' an ately 3650' to 3550 750' in 13-3/8" OD trface in 13-3/8" OD trface in 13-3/8" OD	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing. & 13-3/8" casing. D casing. NECON as 2 1974
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F Well site to possible.	position does not wa manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su be conditioned for	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD arface in 13-3/8" OD arface in 13-3/8" OD to final; inspect APR 25 APR 25 A	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing. & 13-3/8" casing. casing. D casing. D casing. 2 1974 CAL SURVER
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F Well site to possible.	position does not wa manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su be conditioned for	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD arface in 13-3/8" OD arface in 13-3/8" OD to final inspector	ling. Verbal 3, to plug well pen hole. pen hole & 9-5/8"ca Casing. d pull same. in 9-5/8" casing. & 13-3/8" casing. casing. D casing. AFEOn as 21974
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F Cut off 9-5/8 100' Cement F 100' Cement F 50' Cement F Well site to possible. 18. I hereby certify that the foregoing SIGNED	sition does not wa ined from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su be conditioned for main for Main Main Main Main Main Main Main Main	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing. & 13-3/8" casing. casing. D casing. D casing. 2 1974 CAL SURVER
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F Well site to possible. 18. I hereby certify that the foregoin SIGNED A	office use)	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD	<pre>ling. Verbal '3, to plug well '9, to plug well '10, to plug well '</pre>
and structural po approval was obta in the following 200' Cement P 100' Cement P 200' Cement P 100' Cement P 100' Cement P 100' Cement P 100' Cement P 50' Cement P Well site to possible. 18. I hereby certify that the foregoing SIGNED	office use)	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD	ling. Verbal '3, to plug well open hole. open hole & 9-5/8"ca Casing. d pull same. ' in 9-5/8" casing. & 13-3/8" casing. casing. D casing. D casing. 2 1974 CAL SURVER
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F Well site to possible. 18. I hereby certify that the foregoing SIGNED	office use)	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD	<pre>ling. Verbal '3, to plug well '9, to plug well '10, to plug well '</pre>
and structural po approval was obta in the following 200' Cement F 100' Cement F 200' Cement F 200' Cement F 100' Cement F 100' Cement F 100' Cement F 50' Cement F 50' Cement F Well site to possible.	position does not wa ained from Mr. Jame manner: Plug from 14,275' t Plug from 12,940' t Plug from 12,100' t Plug from 4,300' to Plug from approxima Plug from 850' to 7 Plug from 50' to su be conditioned for main for main for TITLE office use) F ANY:	Arrant further dril as A. Knauf, 9-16-7 to 14,075' in 8½" of to 12,840' in 8½" of to 11,900' in 8½" of to 4,200' in 9-5/8" reximately 3600' and ately 3650' to 3550 750' in 13-3/8" OD arface in 13-3/8" OD	<pre>ling. Verbal '3, to plug well '9, to plug well '10, to plug well '</pre>