9–331 (J. b.z. 🕬 🗇 🕼	Bucget Bureau No. 42/R1424
1973 UNITED STA	5. LEASE
DEPARTMENT OF THE INTERIOR	M- 0554956
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas cther	Federal PP 9. WELL NO.
2. NAME OF OPERATOR	1
Mobil Oil Corporation	10. FIELD OR WILDCAT NAME Undestanded (Bone Springs)
3. ADDRESS OF OPERATOR 9 Greenway Plaza, Suite 2700, Hous., TX 77046	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 24, T23S, R26E
below.) AT SURFACE: 1980' FNL & FWL, Sc. 24,T23S,R26E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy NM 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3421' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF Image: Constraint of the second se	VED
SHOOT OR ACIDIZE	10(RBTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-338.)
MULTIPLE COMPLETE	С.
ABANDON* ARTESIA, C	
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Kill Bone Springs w/ 9.5 lb/gal. brine. 2. DOU or (-2, 2/8" the 	
 POH w/ 2-3/8" tbg. Set CIBP @ 6250' and cap w/ 7 sx Class "H" neat cmt. Load hole w/ 9.5 lb/gal. mud laden fluid, using 25 lbs. gel / 1,000 gal. Spot cmt plug 50' above to 100' below liner top using approx. 37 sx Class "H" neat cmt 	
 6. Spot cmt plug from 2600' to 2750' using approx. 54 sx Class "H" cmt. 7. Spot 50' cmt plug at the surface, using approx 18 sx Class "H" cmt. 	
8. Load annulus w/ 9.5 1b/gal. mud; spot a 50' annular plug using approx. 10 sx	
Class "H" neat cmt. 9. Erect P&A monument	
10. Clear location when BLM approval is received.	
Procedure verbally approved by Jim Knauf - USGS Artesia, NM	
Subsurface Safety Valve: Manu. and Type Set @ Ft.	
18. I hereby certify that the foregoing is true and correct SIGNED UNIN TITLE Authorized Agent DATE 12/6/78	
SIGNED DATE DATE	
APPROVED BY APPROVED BYAPPROVED BYAPPRO	
CONDITIONS OF APPROVAL IF ANY:	
*See Instructions on Reverse Side	
	•