

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI  
(Other instruction  
verse side)DATE  
on reForm approved.  
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0415688A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <b>DRILLING</b>	RECEIVED	7. UNIT AGREEMENT NAME <b>OLD INDIAN DRAW UNIT</b>
2. NAME OF OPERATOR <b>Amoco Production Company</b> ✓	DEC - 6 1973	8. FARM OR LEASE NAME <b>7</b>
3. ADDRESS OF OPERATOR <b>BOX 68, HOBBS, N. M. 88240</b>	<b>D. C. C.</b>	9. WELL NO. <b>1</b>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <b>1980' FSLx 1980' FEL Sec. 18, (UNIT J, NW 1/4 SE 1/4)</b>	<b>ARTESIA OFFICE</b>	10. FIELD AND POOL, OR WILDCAT <b>WILDCAT Penn</b>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) <b>3094' R.D.B.</b>	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <b>18-22-28 NMPM</b>
		12. COUNTY OR PARISH <b>EDDY</b>
		13. STATE <b>N.M.</b>

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

**Plug Back**☒

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

DRILLED TO TD of 12,450'. Ran logs. Evaluated. No indicated pays below 3400'. Propose to plug back as follows.

Sx. Plug	Comp.	DEPTH.	Remarks
35 Sx.	Class H	12,100 - 12,200	
35 Sx.	"	10,900 - 11,000	Mud between plugs
35 Sx.	" Neat	9,350 - 9,450	"
50 Sx.	"	5,900 - 6,050	(8 5/8" CSA 5933) "

a casing from BP will be set @ approx 3400'.  
The Delaware sand will be evaluated thru perforations  
to be shot from 3260 - 3290' w/2WSPF.

RECEIVED

NOV 29 1973

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

## 18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

ADMINISTRATIVE ASSISTANT

DATE

11-28-73

(This space for Federal or State office use)

APPROVED BY

DISTRICT ENGINEER

TITLE

DATE

DEC 3 1973

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

0-4. USGS- RST  
1- DIV  
1- SUSP  
1- RRY  
2- MARIATHON  
1- PERRY R BASS