

ELEVATION: KB: 3109'
GL: 3089'


REMEDIAL WORK:

- 12/73 - DST Strawn, 10,195'-300' w/
good gas shows.
- 2/74 - Completion, perf Morrow from
11,346'-557'. Tested well @
2760 MCFD @ 875#. Perf addtnl
Morrow 11,123'-221'. Tested
upper Morrow perfs @ 8 MMCFD
@ 1175#. TA Morrow, perf Strawn
10,276'-284'. Az w/ 2000 gal
15% MS acid w/ 1000 SCF N₂/bbl.
Tested @ 4.15 MMCFD @ 3650#.
Dual completion, Morrow CAOF -
11,192 MCFD, Strawn flow test -
4 MMCFD @ 2825#.
- 1/81 - Tbg communicated, set plug in
pkr above Morrow. Cut off
tbg 11,047'. Ran sleeve over
tbg fish, set Baker Lok-set
pkr @ 11,036'. Attempted
unsuccessfully to pull plug
@ 11,072'. Put Morrow on
prod. through equalizing holes
in plug @ 11,072'. Strawn TA'd.
- 12/84 - Tbg communication, pulled Lok-
set pkr and sleeve. Set Baker
Model DB pkr @ 11,003'. RIH
w/ seal assembly, 946' of tbg,
and Baker Lok-set pkr. Sting
into Model DB and set Lok-set
@ 10,050'.
- 1/86 - Set plug in pkr @ 11,003'.
POOH w/ tbg & Lok-set pkr.
RIH w/ seal assembly, and new
Baker Model A-1 pkr. Could not
fish plug, perf 2 holes in MO
ext @ 11,009.5'. POP.

	SURFACE	INTERMED	INTERMED
SIZE	16"	10 3/4"	7 5/8"
WEIGHT	65#	32#-75#	25.4-33.7
GRADE	H-40	J55/H40	H-80
THREAD	ST&C	ST&C	BUTT/LT&C
DEPTH	350'	1850'	8850'

	LINER
SIZE	5 1/2"
WEIGHT	19.81#
GRADE	S00-95
THREAD	SFJ-P
DEPTH	11634'

PREPRD BY: VINCE DERNBACH
DATE : APRIL 2, 1993



16" SURFACE CASING @ 350'
CMTD W/ 450 SX, 1' TO SURF
W/ 250 SX

10 3/4" INTERMEDIATE CASING @ 1850'
CMT W/ 1080 SX CMT, 1' TO SURF
W/ 400 SX.

7 5/8" CSG XOVER @ 1089'
26.4# ABOVE AND 29.7# BELOW

7 5/8" CSG XOVER @ 3682'
29.7# ABOVE AND 33.7# BELOW

TOP OF 5" LINER @ 8618'

7 5/8" INTERMEDIATE CASING @ 8850'
CMTD W/ 900 SX CMT, TOC @ 2820'

5-1/2" BAKER MODEL A1 PKR @ 10094'

STRAWN PERFS (10276' - 10284') - TA'D

5-1/2" BAKER MODEL DB PKR @ 11003'
PLUG IN F NIPPLE @ 11014' - WELL IS
PROD. THRU HOLES IN TBG @ 11009.5'

TBG CUT @ 11047'

5-1/2" BAKER LOK-SET PKR @ 11072'
PLUG IN MODEL "ER" RECEPTACLE W/
EQUALIZING PORTS OPEN

MORROW PERFS (11123' - 11221')
5-1/2" BAKER MODEL DB PKR @ 11270'
MORROW PERFS (11346' - 11557')

P8TD @ 11593'
5-1/2" LINER @ 11634' CMTD W/ 265 SX
TO @ 11642'