

U. S. STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
N. M. O. C. C. COPY
SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM0405444-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Todd "26" Federal

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Sand Dunes
(Cherry Canyon)11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 26, T-23-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Texas American Oil Corporation ✓

3. ADDRESS OF OPERATOR

1012 Midland Savings Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' FSL & 1980' FEL, Sec. 26-23-S-31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3438.40 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Oil String

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-30-73 to 1-30-74:

T.D. 6100'. Core No. 1 - 5990' - 6046'. Ran 5-1/2" casing to 6100' with 2 stage DV cementing tool at 4303'. Cemented 1st stage with 600 sxs Class C. Could not get DV tool to open. Ran Temp survey. Found top of cement at 4065'. Perf 5-1/2" casing w/2 holes at 4040'. Cemented 2nd stage with 1750 sxs lite wt with 50 sx Class "C". WOC 36 hrs. Drlg cement 3733' - 4303'. Drlg DV tool. Testing casing to 2500#.

RECEIVED

FEB 4 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

February 5, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

FEB 8 - 1974

J. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side