

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

5. LEARN DENOMINATION AND SERIAL NO.

NM-330

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Franklin et al Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Morrow

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec 9, 24-S, 24-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

18. ELEVATIONS (DF, RKB, RT, OR, ETC.)*

19. ELEV. CASINGHEAD

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

25. WAS DIRECTIONAL SURVEY MADE

27. WAS WELL CORRED

No

No

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Otherb. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESER. ☐ Other

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 660' FSL & 2235' FWL, Section 9, 24-S, 24-E

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

APR 29 1974

15. DATE SPUDDED

1-24-74

16. DATE T.D. REACHED

3-9-74

17. DATE COMPL. (Ready to prod.)

4-2-74

18. ELEVATIONS (DF, RKB, RT, OR, ETC.)*

4038' GL

20. TOTAL DEPTH, MD & TVD

10,200'

21. PLUG, BACK T.D., MD & TVD

10,150'

22. IF MULTIPLE COMPL., HOW MANY*

Single

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

9830' to 10,026'

26. TYPE ELECTRIC AND OTHER LOGS RUN

Compensated Acoustic, Density, Neutron, G ord & Forxo

28. CASING RECORD (Report all strings set in well)

CASINO SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48#	299'	17-1/2"	540 sacks (Circulated)	
9-5/8"	36 & 40#	2599'	12-1/4"	950 sacks (Circulated)	
7"	23 & 26#	10,197	8-3/4"	360 sacks (TOC at 8650')	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	9620'	9613'

31. PERFORATION RECORD (Interval, size and number)

Perforated 7" casing with 2, 1/2" JHPF at 9830-40', 9870-76', 9992-10,006', 10,018-10,026'.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
9-30-10,026'	4000 gallons of Morrow Flow acid.

33.*

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
4-2-74		Flowing					Shut In.	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
4-9-74	4	10/64'	→	--	1586	--	--	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
1680#	--	→	--	--	--	--		
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)								

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Area Engineer

DATE April 25, 1974

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 33.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; COBED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
0	2,180'		Dolo & SS	Bone Spring	3,282	
	3,282'		SS	1st Bone Springs	4,500'	
	4,500'		LS	2nd Bone Springs	5,513'	
	4,975'		SS	3rd Bone Springs	6,943'	
	5,513'		LS	Wolfcamp	7,283'	
	5,710'		SS	Penn	7,834'	
	6,943'		LS	Barnett	10,114'	
	7,884'		SS & Shale			
	8,310'		LS			
	8,500'		Shale & LS			
	8,760'		SS, LS & Shale			
	9,470'		LS			
	10,200'		SS, LS & Shale			
SEE ATTACHMENT FOR DST's.						