

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm approved.
Budget Bureau No. 42-R1424.
(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

NM 2020

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Azotea Mesa Unit A

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT
Unders. Bandana Point
Area Morrow11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8-T23S-R24E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Cities Service Oil Company

3. ADDRESS OF OPERATOR

Box 4906 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1780' FSL & 2280' FWL of Sec. 8-T23S-R24E, Eddy Co., New Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3900' GR. (Est.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

T.D. 10,895' Shale. Prep to plug and abandon. This well was drilled to a T.D. of 10,895' and we proposed to plug and abandon in the following manner:

1. Spot a 100 sack cement plug @ approx. 10,601' - T.D. 10,895'.
2. Spot a 35 sack cement plug across top of Morrow @ approx. 10,250' - 10,350'.
3. Spot a 35 sack cement plug across top of Strawn @ approx. 9,450' - 9,550'.
4. Spot a 35 sack cement plug across top of Canyon @ approx. 8,600' - 8,700'.
5. Spot a 35 sack cement plug across top of Dean @ approx. 7,500' - 7,600'.
6. Spot a 35 sack cement plug @ approx. 5,900' - 6,000'.
7. Spot a 35 sack cement plug @ approx. 4,400' - 4,500'.
8. Spot a 35 sack cement plug @ approx. 2,900' - 3,000'.
9. Spot a 35 sack cement plug @ approx. 2,450' - 2,550' (1/2 in and 1/2 out of 8-5/8" csg set and cemented @ 2,500'.)
10. Spot a 10 sack cement surface plug @ approx. 30' - 0' with a 4" dry hole marker.

This plugging procedure was given verbal approval by Mr. Leon Beekman with the U.S.G.S. Office @ Artesia, New Mexico.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Oper. Mgr.

DATE Feb. 12, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side