

Prod Supt _____
Drig Supt _____
Drig Tech _____
Engr _____

Unocal Corp.
Central United States
Business Unit

Date: 8/29/94

Field: Bone Springs (Undesignated)

Asset Group: South

Lease/Unit: Wersell "A"

Well No.: 1

Reason For Work: To Plug and Abandon

Condition of Hole:

Total Depth: 11,815'

PBTD: 10,932'

KB Datum is 18' A/GL:

Casing Record: 13-3/8" @ 400' 48#, 61#, H-40, K-55, Cmt'd w/ 300sx CIRC
9-5/8" @ 5400' 40# N-80, Cmt'd w/ 2650sx. Cmt Circ.
5-1/2" @ 11,815' 17# N-80, SOO-95, Cmt'd w/450sx TOC @ 5455'.

Perforations: **Morrow Perfs.** 11,023-11,696'.
Baker "DB" Pkr w/tbg plug set "F" nple
@ 11,429'. Sand Bailer on top of plug.
CIBP @ 10,932' (CMT CAPPED).
Bone Springs. 8,120-8138'.

Tubing Detail: 263jts (8140'), 2-3/8" 4.7# N-80, A.B. Mod- used tbg@ 8157'. TAC @ 7965' in
12K ten. SN @ 8156'.

Rod & Pmp Detail: None.

Regulatory Requirements: Oil commision notice.

PROCEDURE:

1. MIRU DD PU. ND WH. NU BOP & FNCTN TST. RLSE TAC & TOH W/TBG. PU 5-1/2" RET & RIH ON 2-3/8" TBG. SRA 8,060'. STING OUT RET & CIRC HLE W/10 PPG MLB @ 35 VIS. STING IN RET & SQZ PERFS W/ 100 SX CLASS "C" CMT MIXED @ 14.8 PPG. STING OUT RET & DMP 15 SX ON RET. **PLUG #1:(7912-8138')** TOH.