

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
Mobil Producing TX. & N.M. Inc. /

3. ADDRESS OF OPERATOR  
9 Greenway Pl., Ste 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660 FSL & 1980 FWL  
AT TOP PROD. INTERVAL: Same as surface  
AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

**RECEIVED**  
OCT 1 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM-027994-D  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME RECEIVED  
8. FARM OR LEASE NAME  
Federal RR Com OCT - 5 1981  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME ARTESIA, WHITE  
South Carlsbad Morrow  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 24, T23S, R26E  
12. COUNTY OR PARISH Eddy 13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3234 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-17-81 WIH w/9-5/8 Baker tens pkr, 2-4½ cols on 2-3/8 tbg to 1155. Dump 3x sd down tbg for BP cap @ 5375, press test 9-5/8 csg above and below csg leak @ 740 w/700 psi/held OK, estb inj rate into leak 2 BPM @ 150, cmt'd leak w/500x C 2% ChCl @ 2 BPM, displ cmt to 600, final sqz press 400 psi. Job compl @ 1 PM. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Hooper TITLE Authorized Agent DATE 9-25-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

OCT 2 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO