INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-dilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vortical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate exception state land, where six copies are required. See Bule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

т.	Anhy	T.	Canyon	T.	Ojo Alamo	Т.	Penn. "B"
т.	Salt	. Т.	Strawn 8143'	т.	Kirtland-Fruitland	T.	Penn. "C"
В.	Salt	. T.	Atoka	T.	Pictured Cliffs	Т.	Penn, "D"
т.	Yates	. T.	Miss 9690'	Т.	Cliff House	Т.	Leadville
Т.	7 Rivers	. T.	Devonian 9990 ¹	Т.	Menefee	T.	Madison
							Elbert
Т.	Grayburg	. Т.	Montoya	Т.	Mancos	Т.	McCracken
Т.	San Andres	Τ.	Simpson	Т.	Gallup	Τ.	Ignacio Qtzte
Т.	Glorieta	т.	McKee	. Bas	se Greenhorn	Т.	Granite
Т.	Paddock	Т.	Ellenburger	T.	Dakota	Т.	
Т.	Blinebry	. Т.	Gr. Wash	Τ.	Morrison	Т.	
Т.	Drinkard	Т.	Delaware Sand1400'	Т.	Entrada	Т.	
т.	Abo	. Т.	Bone Springs 2208	Т.	Wingate	Т.	
Т.	Wolfcamp 7308 '	. Т.	Third Bone Springs Se	dr.	Chinle	Т.	
т	Cisco (Bough C)	Т.		T.	Penn. ''A''	Т.	

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0 1,400 2,200 4,230 4,750 6,310 6,610 7,300 7,700 9,100 9,550 9,690 9,930 9,990	2,200 4,230 4,750	2,030 520 1,560 100 690 400	Limestone Sandstone Limestone, Dolomite, & Sha Shale, Limestone & Dolomi Limestone, Dolomite & Sha Sandstone Dolomite Limestone & Shale Sandstone, Limestone, & Sl Shale Limestone & Shale Shale Limestone & Dolomite	te Ie			