

BINDEL COM #1
 4/16 (16) 6285 drlg lm, 8-3/4" hole, 3/4 @ 5985. Fr Wtr.
 BINDEL COM #1
 4/17 (17) 6618 drlg lm, 8-3/4" hole, 1^o @ 6495. Fr Wtr.
 BINDEL COM #1
 4/18 (18) 7070 drlg lm, 8-3/4" hole, 1 1/4 @ 6500. Fr Wtr.
 BINDEL COM #1
 4/19 (19) 7467 drlg lm, 8-3/4" hole, 1 1/2 @ 7000. Fr Wtr.
 BINDEL COM #1
 4/20 (20) 7900 drlg lm, 8-3/4" hole, 2^o @ 7900. Fr Wtr.
 4/22 (22) 8590 drlg lm, 8-3/4" hole, 1-3/4 @ 8250. Fr Wtr.
 BINDEL COM #1
 4/23 (23) 8968 drlg lm, 8-3/4" hole, 1 1/4 @ 8754. Br Wtr.
 BINDEL COM #1
 4/24 (24) 9357 drlg lm, 8-3/4" hole, 1 1/4 @ 9255. Br Wtr.
 BINDEL COM #1
 4/25 (25) 9833 drlg lm & sh, 8-3/4" hole, 3/4 @ 9747. Br Wtr.
 BINDEL COM #1
 4/26 (26) 10,190 ND lm, 8-3/4" hole, NND, 10# Br Wtr
 drlg break 10,180-10,190, circ off gas w/ 400# on ck
 manifold.
 BINDEL COM #1
 4/27 (27) 10,476 drlg lm & sh, 8-3/4" hole, 1/4 @ 10,278, 10.1# Br Wtr.
 fl gas on chokes 5 add'l hrs.
 4/29 (29) 11,075 drlg lm & sh, 8-3/4" hole, 1/2 @ 10,949. 10.1# Br Wtr.
 BINDEL COM #1
 4/30 (30) 11,331 drlg lm & sh, 8-3/4" hole, 3/4 @ 11,288.
 10.1# Br Wtr.
 BINDEL COM #1
 5/1 (31) 11,662 drlg lm & sh, 8-3/4" hole, NND. 10.2-39-8.0.
 BINDEL COM #1
 5/2 (32) 11,864 drlg lm & sh, 8-3/4" hole, NND. 10.2-35-9.4.
 BINDEL COM #1
 5/3 (33) 11,985 drlg lm & sh, 8-3/4" hole, 3/4 @ 11,900.
 10.2-35-6.0.
 BINDEL COM #1
 5/4 (34) 12,173 drlg lm & sh, 8-3/4" hole, NND. 10.5-35-4.0.
 5/6 (36) 12,235 TD lm, 8-3/4" hole, 3/4 @ 12,235, 10.5-38-4.0.
 circ 3 hrs, POH, Schl ran BHC-N-Density-GR & Caliper logs
 0-12,238, loggers TD, then ran Dual LL 5552-12,235, Microlateralog
 & LL from 8900-12,235/14 1/2 hrs, ran bit to bottom, circ past
 8 1/2 hrs.