

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 28 1979

O. C. C.

ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - 111 (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Mobil Oil Corporation ✓

Address of Operator
Nine Greenway Plaza, Suite 2700, Houston, Texas 77046

Location of Well
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM
THE East LINE, SECTION 4 TOWNSHIP 23S RANGE 27E NMPM.

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name
~~Bindel Com~~

8. Farm or Lease Name
Bindel Com.

9. Well No.
1

10. Field and Pool, or Wildcat
Undesignated Wolfcamp

12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3130' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER Plug-back ☒	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Load hole with Lse water
2. Pull out of hole with 2-3/8" tubing, ER receptacles, and seal assembly.
3. Set "DR" plug in Model "D" Packer and cap with 50' cement plug. @ 12075
4. Spot 100' of 5% mud acid (or 4 bbls) from 10200' to 10100'.
5. Perforate the undesignated Eddy County Wolfcamp with 4" casing gun 2 shots/foot 10170 - 80, 10182-92.
6. Go in hole with Retrievable Packer on 2-3/8" tubing - Test tubing going in hole. Set Packer at 10120' (Recommend Baker Model R-3 Double Grip Packer).
7. Swab well in and test.
8. Treat the Wolfcamp with 4000 gals of 15% HCL acid with Nitrogen if necessary.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robbie Jay TITLE Authorized Agent DATE 6/22/79

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 29 1979

CONDITIONS OF APPROVAL, IF ANY: