

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
OCT 11 1974
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. *****
7. Unit Agreement Name *****
8. Farm or Lease Name Bear
9. Well No. 1
10. Field and Pool, or Wildcat Und. So. Carlsbad (Morrow)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Morris R. Antweil ✓
3. Address of Operator Box 2010, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER J , 1650 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 22-S RANGE 27-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3117' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to TD 5375'. Cemented 9-5/8" 36 and 40# J-55 casing @ 5375' w/850 sx Halcolite cement containing 3#/sx flocele and 300 sx. Class "C" neat cement. Plug down 3:30 PM 8 Oct. 74. Top of cement by temperature survey 1850'. WOC 24 hrs. Nippled up. Tested casing and BOP equipment with 2000 psi. for 30 mins. with no decline in pressure. Drilling ahead w/8-3/4" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *R. M. Williams* TITLE **Agent** DATE **10 October, 1974**

APPROVED BY *W. A. Gussert* TITLE **OIL AND GAS INSPECTOR** DATE **OCT 15 1974**

CONDITIONS OF APPROVAL, IF ANY: