



Minimum assembly will consist of two hydraulically operated ram type preventers and a Hydril. If double type preventers are provided, the flanged outlets of the preventer may be used for the flow line and kill line. Minimum operating equipment for the preventers will be: (1) An air operated pump(s) and (2) an accumulator(s) with means of obtaining a fluid charge. A regulator is to be provided for the Hydril preventer. Sufficient fluid capacity in the accumulator(s) shall be available to close all the pressure operated devices at the same time with 25 percent reserve. Hydraulic oil shall be used as the operating fluid. Seamless steel piping shall be used to connect from the closing unit to the preventers. The choke manifold and flow line shall be supported by metal stands. The choke lines shall be anchored. No sharp bends or curves will be permitted in the flow line from the preventers to the pits. Easy and safe access will be maintained to choke manifold at all times. The ram type preventers and hydraulically operated valves will be provided with stem extensions, universal joints, if needed, and operating wheels which are to extend beyond edge of derrick substructure.

Blowout Preventer Equipment

Coquina Oil Corporation
Philly Federal #1
Sec. 21, T23S, R26E
Eddy County, New Mexico

RECEIVED
MAR 19 1974
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

9-9-76 10:05 AM

Leroy Collins called & the well
was shut in @ 9:30 PM

on 9-8-76 - over produced
by 466043 according to Log's schedule