

UNITED STATES N.M.O.C.D. COPY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 12829

6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaparral Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 17-24S-24E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

2310' FNL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4127.3' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Re-entry; production csg ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was drilled to a total depth of 10300' by American Trading & Producing Company. The well was plugged and abandoned in 1974. Yates Petroleum Corporation assumed operation on November 11, 1980. Plugs were drilled as follows:

Surface - 10
3400'-3500'
5058'-5121'
7107'-7257'
8102'-8252'
8972'-9122'

Logged well. TD 10300' Ran 243 joints of 4-1/2" 11.60# K-55 & N-80 LT&C as follows: 48 joints of 4-1/2" 11.60# N-80 LT&C (2041'); 156 joints of 4-1/2" 11.60# K-55 LT&C (6611'); 39 joints of 4-1/2" 11.60# N-80 (1632') (Total 10284') of casing set at 10284'. 1-guide shoe at 10284'. 1-float collar at 10244'. Used 10 centralizers. Cemented w/250 gallons CW-100, 25 sacks 75-25 Poz, 6/10% D-112, 3/10% D-65 and 3# KCL/sack, 600 sacks 50-50 Poz, 6/10% D-112, 3/10% D-65 and 3# KCL/sack. Tailed in w/200 sacks Class H, 6/10% D-112, 3/10% D-65 and 3# KCL/sack. PD 6:00 AM 11-29-80. WOC and tested to 1500 psi, OK. Ran Temperature Survey and found top of cement at 6750'. WLPBTD 10224'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE Dec. 2, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

DEC 4 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side